

DIN EN 13807:2017-05 (E)

Transportable gas cylinders - Battery vehicles and multiple-element gas containers (MEGCs) - Design, manufacture, identification and testing

| Contents | | Page |
|--|---|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Design | 9 |
| 4.1 | General | 9 |
| 4.2 | Mounting | 10 |
| 4.2.1 | Stability (for battery vehicles only) | 10 |
| 4.2.2 | Attachment of pressure receptacles to a chassis | 10 |
| 4.2.3 | Pressure receptacle supports | 10 |
| 4.2.4 | Impact protection | 11 |
| 4.3 | Pressure receptacles | 11 |
| 4.4 | Valves and fittings | 11 |
| 4.5 | Manifold | 12 |
| 4.6 | Main valve(s)/connection(s) | 12 |
| 4.7 | Total assembly | 13 |
| 5 | Manufacturing | 13 |
| 6 | Identification | 13 |
| 6.1 | General | 13 |
| 6.2 | Product and hazard identification | 13 |
| 6.3 | Filling identification | 14 |
| 7 | Type approval, inspection and testing | 14 |
| 7.1 | General | 14 |
| 7.2 | Type approval of battery vehicle or MEGC | 14 |
| 7.2.1 | Design check of the battery vehicle or MEGC | 14 |
| 7.2.2 | Testing of the manifold and battery vehicle or MEGC | 14 |
| 7.2.3 | Flame resistance of cover sheets | 14 |
| 7.2.4 | Conductivity of cover sheets | 14 |
| 7.3 | Initial inspection of fully assembled battery vehicle or MEGC | 15 |
| 7.3.1 | General | 15 |
| 7.3.2 | Manifold | 15 |
| 7.3.3 | Fully assembled battery vehicle or MEGC | 15 |
| 7.3.4 | Identification | 15 |
| 8 | Documentation | 15 |
| Annex A (normative) Specific requirements for dissolved acetylene battery vehicles | | 17 |
| A.1 | General | 17 |
| A.2 | Design | 17 |
| A.2.1 | Material | 17 |
| A.2.2 | Layout | 17 |

| | | |
|--|---|-----------|
| A.2.3 | Acetylene cylinders and acetylene bundles of cylinders | 17 |
| A.2.4 | Cylinder valves | 17 |
| A.2.5 | Manifold | 17 |
| A.2.5.1 | General | 17 |
| A.2.5.2 | Wall thickness of the pipe system | 17 |
| A.2.5.3 | System with wall thickness to withstand detonation and reflection occurring at any point | 18 |
| A.2.5.4 | System to withstand undisturbed detonation with reinforcements at reflection points | 18 |
| A.2.5.5 | Design by means of acetylene decomposition testing | 19 |
| A.2.5.6 | Flexible hoses | 19 |
| A.2.6 | Valves (excluding the cylinder valves and the main valve) | 19 |
| A.2.7 | Safety devices | 19 |
| A.2.7.1 | Design for configurations | 19 |
| A.2.7.2 | Type approval requirement for acetylene decomposition blocker | 20 |
| A.2.8 | Ventilation | 20 |
| A.3 | Identification | 20 |
| A.3.1 | General | 20 |
| A.3.2 | Colour coding | 20 |
| A.3.3 | Filling identification | 20 |
| A.4 | Testing | 21 |
| Annex B (informative) Marking of battery vehicles and MEGCs | | 22 |
| B.1 | General | 22 |
| B.2 | Certification marks | 22 |
| B.3 | Operational marks | 23 |
| Bibliography | | 24 |