DIN EN 1439:2017-10 (E)

LPG equipment and accessories - Procedure for checking transportable refillable LPG cylinders before, during and after filling

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Segregation of cylinders prior to filling 8
4.1 General 8
4.2 Cylinders suitable for filling 8
4.3 Cylinders for periodic inspection 9
4.4 Cylinders requiring further assessment 9

5 Reassessment of cylinders 9

6 Filling conditions 10

7 Post filling checks 10
7.1 Check of filled amount 10
7.2 Action necessary for over/under-filled cylinders 10
7.3 Final checks 10

Annex A (normative) Specific requirements for welded and brazed steel LPG cylinders 11

Annex B (normative) Specific requirements for welded steel LPG cylinders in accordance with EN 14140 or equivalent standard 14

B.1 General 14
B.2 Procedure for establishing rejection criteria for carbon steel cylinders 14
B.3 Rejection criteria for stainless steel cylinders 16

Annex C (normative) Specific requirements for welded aluminium LPG cylinders 19

Annex D (normative) Specific requirements for composite LPG cylinders 22

D.1 Establishment of rejection criteria 22
D.1.1 General 22
D.1.2 Procedure 22
D.2 Examples of rejection criteria 22
D.2.1 Cylinders without a metallic liner 22
D.2.2 Cylinders with a metallic liner 27

Annex E (normative) Safe filling conditions 31

Annex F (normative) Flow diagram of the checks before, during and after filling 32

Annex G (normative) Specific inspection procedure for over-moulded cylinder (OMC) 33

G.1 Application and cylinder description 33
G.2 Cylinders suitable for filling 33
G.3 Cylinders for periodic inspection 33
G.4 Cylinders requiring further assessment 33
G.5 Reassessment of cylinders 33

Annex H (informative) Example of an Over-Moulded Cylinder 35

Bibliography 36