

DIN EN 1439:2017-10 (E)

LPG equipment and accessories - Procedure for checking transportable refillable LPG cylinders before, during and after filling

Contents	Page
European foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
4 Segregation of cylinders prior to filling	8
4.1 General	8
4.2 Cylinders suitable for filling	8
4.3 Cylinders for periodic inspection	9
4.4 Cylinders requiring further assessment	9
5 Reassessment of cylinders	9
6 Filling conditions	10
7 Post filling checks	10
7.1 Check of filled amount	10
7.2 Action necessary for over/under-filled cylinders	10
7.3 Final checks	10
Annex A (normative) Specific requirements for welded and brazed steel LPG cylinders	11
Annex B (normative) Specific requirements for welded steel LPG cylinders in accordance with EN 14140 or equivalent standard	14
B.1 General	14
B.2 Procedure for establishing rejection criteria for carbon steel cylinders	14
B.3 Rejection criteria for stainless steel cylinders	16
Annex C (normative) Specific requirements for welded aluminium LPG cylinders	19
Annex D (normative) Specific requirements for composite LPG cylinders	22
D.1 Establishment of rejection criteria	22
D.1.1 General	22
D.1.2 Procedure	22
D.2 Examples of rejection criteria	22
D.2.1 Cylinders without a metallic liner	22
D.2.2 Cylinders with a metallic liner	27
Annex E (normative) Safe filling conditions	31
Annex F (normative) Flow diagram of the checks before, during and after filling	32
Annex G (normative) Specific inspection procedure for over-moulded cylinder (OMC)	33

G.1	Application and cylinder description	33
G.2	Cylinders suitable for filling	33
G.3	Cylinders for periodic inspection	33
G.4	Cylinders requiring further assessment	33
G.5	Reassessment of cylinders	33
Annex H (informative) Example of an Over-Moulded Cylinder		35
Bibliography		36