

ISO 15995:2019 (E)

Gas cylinders — Specifications and testing of LPG cylinder valves — Manually operated

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Design and specification |
| 4.1 | General |
| 4.2 | Materials |
| 4.2.1 | General |
| 4.2.2 | Operating temperatures |
| 4.2.3 | Copper alloys |
| 4.2.4 | Non-metallic materials |
| 4.3 | Essential components |
| 4.3.1 | Valve operating mechanism |
| 4.3.2 | Valve body |
| 4.3.3 | Valve stem |
| 4.3.4 | Valve outlet |
| 4.3.5 | Excess flow valve |
| 4.4 | Optional components |
| 4.4.1 | General |
| 4.4.2 | Pressure relief valve |
| 4.4.3 | Reduction tube |
| 4.4.4 | Fixed liquid level gauge |
| 4.4.5 | Excess flow valve |
| 4.4.6 | Non-return valve |
| 4.4.7 | Liquid level indicator |
| 4.4.8 | Sealing cap and sealing plug |
| 4.4.9 | Sediment tube |
| 4.5 | Leak tightness |
| 4.6 | Operating torque |
| 4.7 | Closing torque |
| 4.8 | Opening torque |
| 5 | Valve type test |
| 5.1 | General |
| 5.2 | Test samples |
| 5.3 | Test procedure and test requirements |
| 5.4 | Inspection |
| 5.5 | Hydraulic pressure test |
| 5.5.1 | Procedure |
| 5.5.2 | Requirement |
| 5.6 | External and internal leak tightness tests |
| 5.6.1 | Procedure |
| 5.6.1.1 | General |
| 5.6.1.2 | External leak tightness test |
| 5.6.1.3 | Internal leak tightness test |
| 5.6.2 | Requirement |
| 5.7 | Valve stem test |

| | |
|---------|--|
| 5.7.1 | Procedure |
| 5.7.2 | Requirement |
| 5.8 | Hand wheel fire exposure test |
| 5.8.1 | Procedure |
| 5.8.2 | Requirement |
| 5.9 | Impact test |
| 5.9.1 | General |
| 5.9.2 | Procedure |
| 5.9.3 | Requirement |
| 5.10 | Excessive closing torque test |
| 5.10.1 | Procedure |
| 5.10.2 | Requirement |
| 5.11 | Excessive opening torque test |
| 5.11.1 | Procedure |
| 5.11.2 | Requirement |
| 5.12 | Endurance test |
| 5.12.1 | Procedure |
| 5.12.2 | Requirement |
| 5.13 | Examination of dismantled valves |
| 5.13.1 | Procedure |
| 5.13.2 | Requirement |
| 5.14 | Excess flow valve test |
| 5.14.1 | General |
| 5.14.2 | Excess flow valve test with air |
| 5.14.3 | Excess flow valve test with water |
| 5.14.4 | Excess flow strength test |
| 5.15 | Non-return valve test |
| 5.15.1 | Procedure |
| 5.15.2 | Requirement |
| 5.16 | Vibration test |
| 5.16.1 | Procedure |
| 5.16.2 | Requirement |
| 6 | Documentation and test report |
| 6.1 | Documentation |
| 6.2 | Test report |
| 7 | Production testing |
| 8 | Markings |
| Annex A | (normative) Special valves |
| A.1 | General |
| A.2 | Excessive torque tests (5.10 and 5.11) |
| A.2.1 | Procedure |
| A.2.2 | Requirement |
| A.3 | Endurance test (5.12) |
| A.3.1 | Procedure |
| A.3.2 | Requirement |
| A.4 | Leak tightness test |
| Annex B | (normative) Production testing and inspection |
| Annex C | (normative) Special low temperature requirements |
| Annex D | (normative) Vibration testing |
| D.1 | General |
| D.2 | Test samples |
| D.3 | Test method |