

ISO/TR 13086-4:2019 (E)

Gas cylinders — Guidance for design of composite cylinders — Part 4: Cyclic fatigue of fibres and liners

Contents

| | |
|---------|--|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Background |
| 5 | Cyclic fatigue evaluation |
| 6 | Elements of cyclic fatigue |
| 6.1 | Service conditions and requirements |
| 6.1.1 | Temperature and moisture |
| 6.1.2 | Pressure |
| 6.1.3 | Pressure cycles |
| 6.2 | Test conditions and specimens |
| 6.3 | Fibre materials and their fatigue properties |
| 6.3.1 | Materials |
| 6.3.2 | Material properties and data |
| 6.3.3 | Hybrid construction |
| 6.4 | Liner materials and their fatigue properties |
| 6.4.1 | Materials used |
| 6.4.2 | Material properties and data |
| 6.4.3 | Issues with localized strain differences |
| 6.5 | Resin materials and their fatigue properties |
| 6.6 | Composite/liner load sharing |
| 6.7 | Autofrettage |
| 6.8 | Analysis methods |
| 6.9 | Leak before burst (LBB) |
| 6.10 | Damage tolerance |
| 6.11 | Aging and environment |
| 6.12 | Counting cycles |
| 6.13 | Combining cycles |
| 6.14 | Qualification testing |
| 7 | Summary and conclusions |
| Annex A | (informative) Equivalent pressure cycling |
| A.1 | Purpose |
| A.2 | Developing an S-N diagram |
| A.3 | Equivalent pressure cycling |
| A.4 | Developing a Goodman diagram |

Page count: 20