

ISO 11119-2:2020 (E)

Gas cylinders — Design, construction and testing of refillable composite gas cylinders and tubes — Part 2: Fully wrapped fibre reinforced composite gas cylinders and tubes up to 450 l with load-sharing metal liners

Contents

| | |
|-----------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols |
| 5 | Inspection and testing |
| 6 | Materials |
| 6.1 | Liner materials |
| 6.2 | Composite materials |
| 7 | Design and manufacture |
| 7.1 | General |
| 7.2 | Design submission |
| 7.3 | Manufacturing |
| 8 | Type approval procedure |
| 8.1 | General requirements |
| 8.2 | Prototype tests |
| 8.3 | New design |
| 8.4 | Design variants |
| 8.5 | Type approval test procedures and criteria |
| 8.5.1 | Proof pressure test |
| 8.5.1.1 | Procedure |
| 8.5.1.2 | Criteria |
| 8.5.2 | Hydraulic volumetric expansion test |
| 8.5.2.1 | Procedure |
| 8.5.2.2 | Criteria |
| 8.5.3 | Liner burst test |
| 8.5.3.1 | Procedure |
| 8.5.3.2 | Criteria |
| 8.5.4 | Cylinder burst test |
| 8.5.4.1 | Procedure |
| 8.5.4.2 | Criteria |
| 8.5.5 | Ambient cycle test |
| 8.5.5.1 | For cylinders with test pressure equal to or greater than 60 bar |
| 8.5.5.1.1 | General |
| 8.5.5.1.2 | Procedure |
| 8.5.5.1.3 | Criteria |
| 8.5.5.2 | For cylinders with test pressure less than 60 bar |
| 8.5.5.2.1 | Procedure |
| 8.5.5.2.2 | Criteria |
| 8.5.6 | Environmental cycle test |
| 8.5.6.1 | General |
| 8.5.6.2 | Procedure |

- 8.5.6.3 Criteria
 - 8.5.7 Flaw test
 - 8.5.7.1 Procedure
 - 8.5.7.2 Criteria
 - 8.5.8 Drop/impact test
 - 8.5.8.1 General
 - 8.5.8.2 For cylinders up to and including 50 l water capacity with unspecified gas service and cylinders with liquefied gas service
 - 8.5.8.2.1 Procedure
 - 8.5.8.2.2 Criteria
 - 8.5.8.3 For cylinders up to and including 50 l water capacity with dedicated compressed gas service
 - 8.5.8.3.1 Procedure
 - 8.5.8.3.2 Criteria
 - 8.5.8.4 For cylinders over 50 l water capacity
 - 8.5.8.4.1 Procedure
 - 8.5.8.4.2 Criteria
 - 8.5.8.5 For tubes over 150 l water capacity
 - 8.5.8.5.1 Procedure
 - 8.5.8.5.2 Criteria
 - 8.5.9 High velocity impact (gunfire) test
 - 8.5.9.1 Procedure
 - 8.5.9.2 Criteria
 - 8.5.10 Fire resistance test
 - 8.5.10.1 General
 - 8.5.10.2 Procedure
 - 8.5.10.2.1 General
 - 8.5.10.2.2 Horizontal test
 - 8.5.10.2.3 Vertical test
 - 8.5.10.3 Criteria
 - 8.5.11 Salt water immersion test
 - 8.5.11.1 General
 - 8.5.11.2 Procedure
 - 8.5.11.3 Criteria
 - 8.5.12 Torque test
 - 8.5.12.1 General
 - 8.5.12.2 Procedure
 - 8.5.12.3 Criteria
 - 8.5.13 Environmentally assisted stress rupture test
 - 8.5.13.1 Procedure
 - 8.5.13.2 Criteria
 - 8.5.14 Resin shear strength
 - 8.5.15 Glass transition temperature
 - 8.6 Failure of type approval tests
- 9 Batch inspection and testing**
- 9.1 Liner
 - 9.2 Failure of liner batch tests
 - 9.3 Overwrap materials
 - 9.4 Composite cylinder
 - 9.5 Cylinder failure during type approval or batch testing
- 10 Cylinder marking**
- 10.1 General
 - 10.2 Additional marking
- Annex A (informative) Examples of design approval certificate**
- Annex B (informative) Specimen test reports**
- Annex C (informative) Test report for equivalency**
- Annex D (informative) Standardized test requirements for thermally activated pressure relief devices**
- D.1 General

- D.2 Cylinder test**
- D.2.1 Cylinder set-up**
- D.2.2 Fire source**
- D.2.3 Temperature and pressure measurements**
- D.2.4 General test requirements**
- D.2.5 Test options**
- D.2.5.1 Option A — Controlled release of pressure**
- D.2.5.2 Option B — Fire test until rupture**
- D.3 PRD test**
- D.4 Vent test**
- D.5 System assessments**
- D.5.1 Qualification limit envelope**
- D.5.2 Service limit envelope**
- D.5.3 Acceptable results**

Page count: 43