

DIN EN ISO 407:2021-09 (E)

Small medical gas cylinders - Pin-index yoke-type valve connections (ISO 407:2021)

| Contents | | Page |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| European foreword | | 3 |
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Valve | 5 |
| 5 | Yoke | 6 |
| 6 | Basic dimensions | 6 |
| 6.1 | General | 6 |
| 6.2 | Pin-index yoke-type valve body | 7 |
| 6.3 | Single-pin yoke-type valve connection system | 8 |
| 6.4 | Two-pin yoke-type valve connection system with the pins in a single row | 8 |
| 6.5 | Two-pin yoke-type valve connection system with the pins in a double row | 9 |
| 6.6 | Basic dimensions | 9 |
| 7 | Requirements for alternative designs of yoke-type valve connections | 10 |
| 7.1 | Requirements for the design of the connecting yoke | 10 |
| 7.2 | Examples of alternative construction for the connecting yoke | 10 |
| 8 | Dimensions and positions of the holes and pins for yoke-type valve connections | 13 |
| 8.1 | General | 13 |
| 8.2 | Outlet connection with single-pin system | 13 |
| 8.3 | Outlet connections with two-pin/single-row system | 14 |
| 8.3.1 | Outlet connection for oxygen | 14 |
| 8.3.2 | Outlet connection for oxygen/carbon dioxide mixture (CO 7 %)2 | 15 |
| 8.3.3 | Outlet connection for oxygen/helium mixture (He 80 %) | 15 |
| 8.3.4 | Outlet connection for ethylene | 16 |
| 8.3.5 | Outlet connection for nitrous oxide (with or without liquid draw-off) | 16 |
| 8.3.6 | Outlet connection for cyclopropane | 17 |
| 8.3.7 | Outlet connection for helium and for helium/oxygen mixture (O < 20 %)2 | 17 |
| 8.3.8 | Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture (CO > 7 %)2 | 18 |
| 8.3.9 | Outlet connection for medical air | 18 |
| 8.3.10 | Outlet connection for nitrogen | 19 |
| 8.4 | Outlet connection with two-pin/double-row system | 19 |