

DIN EN 17527:2022-05 (E)

Helium cryostats - Protection against excessive pressure

Contents		Page
European foreword		6
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms and definitions	8
4	Symbols	14
5	Process flow-charts	18
5.1	Process flow-chart concerning risk assessment and protection concepts	18
5.2	Process flow-chart concerning scenario-specific dimensioning of helium circuit PRD	20
6	Risk assessment	21
6.1	General information on risk assessment	21
6.2	Sources of excessive pressure rise relevant for dimensioning	21
6.2.1	Loss of insulating vacuum	21
6.2.2	Loss of beamline vacuum	21
6.2.3	Quench of superconducting device	21
6.2.4	Leak of cryogenic fluid	22
6.2.5	Dielectric breakdown	22
6.2.6	Entrapment of cryogenic fluid	22
6.3	Sources of excessive pressure rise to be mitigated	22
6.3.1	Thermal acoustic oscillation	22
6.3.2	Cryopumping	23
6.3.3	Power failure	23
6.3.4	Pressure surge	23
6.3.5	Freezing	23
6.3.6	Backflow	23
6.3.7	Other sources of excessive pressure	23
6.3.8	Earthquake	24
6.3.9	Fire	24
6.4	Combined scenarios	24
6.5	Risk assessment before ordering	24
6.6	Risk assessment in the design phase	25
7	Protection concepts	25
7.1	General	25
7.2	Single-stage protection concept	25
7.3	Multi-stage protection concepts	26
7.3.1	General	26
7.3.2	Pressure protection of high-pressure helium cryostats	27
7.3.3	Pressure protection of low-pressure helium cryostats	27
7.3.4	Pressure protection of sub-atmospheric helium cryostats	28
7.3.5	Pressure protection of He-II cryostats	28
7.3.6	Pressure protection of ultra-low temperature refrigerator systems	28
8	Dimensioning of pressure relief devices	28
8.1	Method for the dimensioning of pressure relief devices	28

8.2	Calculation of the minimum discharge area	29
8.3	Calculation of the fluid state properties at relieving conditions	29
8.3.1	Calculation of the relieving pressure	29
8.3.2	Calculation of the specific volume	30
8.4	Calculation of the relieving mass flow rate	32
8.4.1	General	32
8.4.2	Loss of insulating vacuum	33
8.4.3	Loss of beamline vacuum	33
8.4.4	Quench of a superconducting device	34
8.4.5	Leak of cryogenic fluid	37
8.4.6	Dielectric breakdown	38
8.4.7	Calculation of the specific enthalpy change	38
8.5	Calculation of the mass flux	39
8.5.1	General	39
8.5.2	Influence of upstream pipework	41
8.5.3	Influence of downstream pipework	42
8.6	Calculation of the discharge coefficient	42
8.6.1	General	42
8.6.2	Adaption of the discharge coefficient of PRV	43
8.7	Transfer line systems	43
8.8	Dimensioning of vacuum vessel PRD	43
9	Pressure relief devices	44
9.1	General	44
9.2	Pressure relief valves	44
9.3	Bursting discs	45
9.4	Combinations of pressure relief valves and bursting discs	45
9.5	Magnetic pressure relief devices	45
9.6	Pressure relief devices for insulating vacuum vessels	45
9.7	Mechanical supports for pressure relief devices	45
9.8	Materials for pressure relief devices	46
10	Substance release	46
10.1	General	46
10.2	Discharge lines and discharge systems	46
11	Operating, maintenance and inspection instructions	46
11.1	General	46
11.2	Specific instructions to be included in the operating, maintenance and inspection instructions	47
Annex A (informative) Thermodynamic characteristics of helium		48
A.1	Basics	48
A.2	Process path during relieving	49
Annex B (informative) Additional information on risk assessment		52
B.1	Loss of insulating vacuum	52
B.2	Loss of beamline vacuum	54
B.3	Quench of superconducting device	54
B.3.1	General	54
B.3.2	Main cooling scenarios	56
B.4	Leak of cryogenic fluid	57
B.4.1	General	57
B.4.2	Leak-before-break behaviour	57
B.4.3	Material characteristics	57
B.4.4	Thermo-mechanical stress	58
B.5	Dielectric breakdown	58
B.6	Thermal acoustic oscillation	59
B.7	Cryopumping	61
B.8	Qualitative risk assessment	61

B.8.1	General	61
B.8.2	Probability level	64
B.8.3	Severity level	65
B.8.4	Criticality matrix	65
B.8.5	HAZOP table	67
Annex C (informative) Protection concepts		68
C.1	Single-stage protection concept	68
C.2	Multi-stage protection concepts	69
C.2.1	General	69
C.2.2	Pressure protection of superconducting magnet systems	69
C.2.3	Pressure protection of superconducting radiofrequency cavities	71
C.2.4	Pressure protection of sub-atmospheric helium systems	72
C.2.5	Pressure protection of He-II systems	73
C.2.6	Pressure protection of ultra-low temperature refrigerator systems	74
Annex D (informative) Dimensioning of pressure relief devices		76
D.1	Equivalence between EN ISO 4126-7:2013/A1:2016/EN ISO 21013-3:2016 and D.276 D.2 Case-specific model for the dimensioning of pressure relief devices	80
D.2.1	General	80
D.2.2	Calculation of the minimum discharge area	80
D.2.3	Determination of the fluid velocity	80
D.2.4	Calculation of the discharge function	81
D.3	Influence of upstream pipework	83
D.4	Coefficient of discharge	85
D.5	Exemplary calculations of the minimum flow area	85
D.5.1	Example 1 - Vertical He-I magnet cryostat	85
D.5.2	Example 1 with the influence of downstream pipework	91
D.5.3	Example 2 - Superfluid He-II cryostat protected by two PRD in series - Subcritical relief ...	92
D.5.4	Example 3 - Superfluid He-II cryostat protected by two PRD in series - Supercritical relief	99
Annex E (informative) Types of pressure relief devices		106
E.1	Application standards	106
E.2	Product standards	107
E.2.1	Purpose, prerequisites	107
E.2.2	Full-lift pressure relief valves	109
E.2.3	Standard pressure relief valves	110
E.2.4	Proportional pressure relief valves	110
E.2.5	Pilot-operated pressure relief valves	110
E.2.6	Controlled pressure relief valves with an additional pneumatic load	111
E.2.7	PRV with magnetic actuation	111
E.2.8	Specific cryogenic PRV features	112
E.3	Bursting discs	113
E.3.1	Functional characteristics	113
E.3.2	Metal bursting discs	113
E.3.3	Graphite bursting discs	114
E.3.4	Long-term behaviour	114
E.3.5	Leak rates	115
E.4	Pressure relief valve / bursting disc combinations	115
E.5	Pressure relief devices for vacuum vessels	116
Bibliography		117