

ISO 11515:2022-08 (E)

Gas cylinders - Refillable composite reinforced tubes of water capacity between 450 l and 3000 l - Design, construction and testing

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols	5
5	Inspection and testing	6
6	Materials	6
6.1	Liner materials	6
6.2	Composite overwrap	7
7	Design and manufacture	7
7.1	General	7
7.2	Design submission	8
7.3	Manufacturing	9
8	Type approval procedure	10
8.1	General	10
8.2	Prototype tests	10
8.3	New design	11
8.4	Design variants	12
8.5	Type approval test procedures and criteria	17
8.5.1	General	17
8.5.2	Hydraulic proof pressure test	17
8.5.3	Hydraulic volumetric expansion test	17
8.5.4	Liner burst test	18
8.5.5	Tube burst test	18
8.5.6	Ambient cycle test	19
8.5.7	Environmental cycle test	20
8.5.8	Flaw test	21
8.5.9	Blunt impact test	23
8.5.10	Fire resistance test	24
8.5.11	Neck strength test	26
8.5.12	Leak test	27
8.5.13	Accelerated stress rupture test	27
8.5.14	Permeability test	28
8.5.15	Gas cycle test	28
8.5.16	Coatings test	29
8.5.17	Salt spray test	30
8.5.18	Acid environment test	30
8.5.19	Vacuum test	31
8.5.20	High velocity impact (gunfire) test	31
8.5.21	Glass transition temperature test	32
8.5.22	Resin shear strength test	32

8.6	Failure of type approval tests	32
9	Inspection and testing at time of manufacture	32
9.1	Liners for Type 2 and Type 3 tubes	32
9.2	Failure of load-sharing liner batch tests	33
9.3	Liners for Type 4 tubes	33
9.4	Failure of non-load sharing liner batch tests	34
9.5	Overwrap materials	34
9.6	Composite tube	35
9.7	Failure of batch tests	35
10	Tube marking	36
10.1	General	36
10.2	Additional marking	36
Annex A (informative) Example of a design approval certificate		37
Annex B (informative) Example of a test report		38
Annex C (normative) Ultrasonic inspection for seamless steel liners and metal tubing		40
Annex D (informative) Guidance for calculating permeation rates when using trace gases		44
Bibliography		45