

ISO 407:2023-07 (E)

Small medical gas cylinders - Pin-index yoke-type valve connections

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Valve	1
5	Yoke	2
6	Basic dimensions	2
6.1	General	2
6.2	Pin-index yoke-type valve body	3
6.3	Single-pin yoke-type valve connection system	4
6.4	Two-pin yoke-type valve connection system with the pins in a single row	4
6.5	Two-pin yoke-type valve connection system with the pins in a double row	5
6.6	Basic dimensions	5
7	Requirements for alternative designs of yoke-type valve connections	6
7.1	Requirements for the design of the connecting yoke	6
7.2	Examples of alternative construction for the connecting yoke	6
8	Dimensions and positions of the holes and pins for yoke-type valve connections	9
8.1	General	9
8.2	Outlet connection with single-pin system	9
8.3	Outlet connections with two-pin/single-row system	10
8.3.1	Outlet connection for oxygen	10
8.3.2	Outlet connection for oxygen/carbon dioxide mixture (CO₂ 7 %)	11
8.3.3	Outlet connection for oxygen/helium mixture (He 80 %)	11
8.3.4	Outlet connection for ethylene	12
8.3.5	Outlet connection for nitrous oxide (with or without liquid draw-off)	12
8.3.6	Outlet connection for cyclopropane	13
8.3.7	Outlet connection for helium and for helium/oxygen mixture (O₂ < 20 %)	13
8.3.8	Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture (CO₂ > 7 %)	14
8.3.9	Outlet connection for medical air	14
8.3.10	Outlet connection for nitrogen	15
8.4	Outlet connection with two-pin/double-row system	15