

# DIN EN ISO 407:2023-12 (E)

## Small medical gas cylinders - Pin-index yoke-type valve connections (ISO 40 7:2023)

---

### Contents

Page

European foreword	3
Foreword	4
<b>1</b> Scope	<b>5</b>
<b>2</b> Normative references	<b>5</b>
<b>3</b> Terms and definitions	<b>5</b>
<b>4</b> Valve	<b>5</b>
<b>5</b> Yoke	<b>6</b>
<b>6</b> Basic dimensions	<b>6</b>
6.1 General	6
6.2 Pin-index yoke-type valve body	7
6.3 Single-pin yoke-type valve connection system	8
6.4 Two-pin yoke-type valve connection system with the pins in a single row	8
6.5 Two-pin yoke-type valve connection system with the pins in a double row	9
6.6 Basic dimensions	9
<b>7</b> Requirements for alternative designs of yoke-type valve connections	<b>10</b>
7.1 Requirements for the design of the connecting yoke	10
7.2 Examples of alternative construction for the connecting yoke	10
<b>8</b> Dimensions and positions of the holes and pins for yoke-type valve connections	<b>13</b>
8.1 General	13
8.2 Outlet connection with single-pin system	13
8.3 Outlet connections with two-pin/single-row system	14
8.3.1 Outlet connection for oxygen	14
8.3.2 Outlet connection for oxygen/carbon dioxide mixture ( $\text{CO}_2 \leq 7\%$ )	15
8.3.3 Outlet connection for oxygen/helium mixture ( $\text{He} \leq 80\%$ )	15
8.3.4 Outlet connection for ethylene	16
8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off)	16
8.3.6 Outlet connection for cyclopropane	17
8.3.7 Outlet connection for helium and for helium/oxygen mixture ( $\text{O}_2 < 20\%$ )	17
8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture ( $\text{CO}_2 > 7\%$ )	18
8.3.9 Outlet connection for medical air	18
8.3.10 Outlet connection for nitrogen	19
8.4 Outlet connection with two-pin/double-row system	19