

DIN EN ISO 407:2023-12 (E)

Small medical gas cylinders - Pin-index yoke-type valve connections (ISO 40 7:2023)

Contents

Page

European foreword	3
Foreword	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Valve	5
5 Yoke	6
6 Basic dimensions	6
6.1 General	6
6.2 Pin-index yoke-type valve body	7
6.3 Single-pin yoke-type valve connection system	8
6.4 Two-pin yoke-type valve connection system with the pins in a single row	8
6.5 Two-pin yoke-type valve connection system with the pins in a double row	9
6.6 Basic dimensions	9
7 Requirements for alternative designs of yoke-type valve connections	10
7.1 Requirements for the design of the connecting yoke	10
7.2 Examples of alternative construction for the connecting yoke	10
8 Dimensions and positions of the holes and pins for yoke-type valve connections	13
8.1 General	13
8.2 Outlet connection with single-pin system	13
8.3 Outlet connections with two-pin/single-row system	14
8.3.1 Outlet connection for oxygen	14
8.3.2 Outlet connection for oxygen/carbon dioxide mixture ($\text{CO}_2 \leq 7\%$)	15
8.3.3 Outlet connection for oxygen/helium mixture ($\text{He} \leq 80\%$)	15
8.3.4 Outlet connection for ethylene	16
8.3.5 Outlet connection for nitrous oxide (with or without liquid draw-off)	16
8.3.6 Outlet connection for cyclopropane	17
8.3.7 Outlet connection for helium and for helium/oxygen mixture ($\text{O}_2 < 20\%$)	17
8.3.8 Outlet connection for carbon dioxide (with or without liquid draw-off) and for carbon dioxide/oxygen mixture ($\text{CO}_2 > 7\%$)	18
8.3.9 Outlet connection for medical air	18
8.3.10 Outlet connection for nitrogen	19
8.4 Outlet connection with two-pin/double-row system	19