

DIN EN 12817:2006-06 (E)

LPG equipment and accessories - Inspection and requalification of LP G tanks up to and including 13 m<(hoch)3> overground

Contents		Page
Introduction		5
1	Scope	5
2	Terms and definitions	5
3	Safety	6
3.1	Safety precautions	6
3.2	Unsafe conditions	6
3.3	Leaks	6
4	Written scheme	6
5	Tank inspection and re-qualification	7
5.1	Routine inspection	7
5.2	Periodic inspection	7
5.3	Re-qualification	7
6	Inspection of tank and tank fittings	8
6.1	Tank	8
6.2	Tank fittings and immediate pipework	8
6.3	Valve cover	9
6.4	Bonding	9
6.5	Pressure relief valve	9
6.6	Pressure gauge	9
6.7	Contents gauges	9
6.8	Shut-off valves	9
6.9	Studs, bolts, nuts, and washers	9
7	Site inspection	10
7.1	Storage site	10
7.2	Piers and foundations	10
7.3	Warning notices	10
8	Competence	10
8.1	Routine inspection	10
8.2	Periodic inspection	10
8.3	Re-qualification	10
9	Records	10
9.1	Tank data	10
9.2	Reports	11
Annex A (informative) Visual inspection		12
A.1	Internal and external visual inspections	12
A.2	Inspection techniques	12
A.2.1	External inspection	12
A.2.2	Internal inspection	12
A.3	Records	12
A.4	Additional inspection	12

Annex B (informative) Hydraulic pressure test	14
Annex C (informative) Acoustic emission examination during proof testing	15
C.1 General	15
C.2 Safety precautions	15
C.3 Acceptance criteria	16
Annex D (informative) Ultrasonic thickness test	17
D.1 General	17
D.2 Apparatus setting	17
D.3 Control measurement	17
D.4 Shell thickness measurements	17
D.5 End thickness	17
D.6 Interpretation	17
D.7 Rejection criteria	18
Annex E (informative) Assessment of tanks by sampling	19
E.1 General	19
E.2 Homogeneous batch	19
E.3 Selection of samples	19
E.4 Sample selection	20
E.5 Inspection period	20
E.6 Presentation of results and decisions	20
E.7 Pass criteria	20
E.8 Example calculation of a sample	20
Annex F (informative) Example of a report	22
Annex ZA (informative) A-deviations	23