

DIN EN 14197-2:2006-11 (E)

Cryogenic vessels - Static non-vacuum insulated vessels - Part 2: Design, fabrication, inspection and testing

Contents		Page
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions and symbols	8
3.1	Terms and definitions	8
3.2	Symbols	9
4	Design	10
4.1	Design options	10
4.2	Common design requirements	10
4.3	Design by calculation	14
5	Fabrication	47
5.1	General	47
5.2	Cutting	47
5.3	Cold forming	47
5.4	Hot forming	48
5.5	Manufacturing tolerances	49
5.6	Welding	52
5.7	Non-welded permanent joints	53
6	Inspection and testing	54
6.1	Quality plan	54
6.2	Production control test plates	54
6.3	Non-destructive testing	56
6.4	Rectification	59
6.5	Pressure testing	60
Annex A (normative) Elastic stress analysis		61
A.1	General	61
A.2	Terminology	61
A.3	Limit for longitudinal compressive general membrane stress	63
A.4	Stress categories and stress limits for general application	64
A.5	Specific criteria, stress categories and stress limits for limited application	65
Annex B (normative) Additional Requirements for 9 % Ni steel		70
B.1	Introduction	70
B.2	Specific requirements	70
Annex C (Informative) Pressure strengthening of vessels from austenitic stainless steels		72
C.1	Introduction	72
C.2	Field of application	72
C.3	Definitions and units of measurement	72
C.4	Materials	73
C.5	Design	74

C.6	Manufacturing and inspection	77
C.7	Comments	78
Annex D (informative) Pressure limiting systems		84
Annex E (informative) Specific weld details		85
E.1	Field of application	85
E.2	Specific weld detail	85
E.3	Oxygen service requirements	86
Annex F (normative) Additional requirements for flammable fluids		89
Annex G (informative) Increased material property for austenitic stainless steel		90
Annex H (normative) Base materials		91
Annex I (informative) Other materials		93
Annex ZA (informative) Clauses of this European Standard addressing essential requirements or other provisions of EU Directives		95
Figures Figure 1 - Stiffening rings		24
Figure 2 - Sectional materials stiffeners		24
Figure 3 - Dished ends		25
Figure 4 a) - Unpierced dished end		25
Figure 4 b) - Dished end with nozzle		25
Figure 4 c) - End with knuckle and crown of unequal wall thickness		26
Figure 4 d) -- Weld outside 0,6 Da		26
Figure 4 e) -- Weld inside 0,6 Da		26
Figure 4 f) -- End welded together from round plate and segments		27
Figure 5 -- Design factors for 10 % torispherical dished ends		27
Figure 6 -- Design factors for 2:1 torispherical dished ends		28
Figure 7 a) -- Geometry of convergent conical shells		28
Figure 7 b) -- Geometry of a divergent conical shell		29
Figure 8 -- Geometry of a cone opening		29
Figure 9 -- Geometrical dimensions in the case of loading by external pressure		29
Figure 10.1 - Permissible value v_K pS 15 for convergent cone with an opening angle = 10°		30
Figure 10.2 - Permissible value v_{15K} pS or convergent cone with an opening angle = 20°		31
Figure 10.3 - Permissible value v_{15K} pS for convergent cone with an opening angle = 30°		32
Figure 10.4 - Permissible value v_{15K} pS for convergent cone with an opening angle = 40°		33
Figure 10.5 - Permissible value v_{15K} pS for convergent cone with an opening angle = 50°		34

Figure 10.6 - Permissible value v_{15K} pS for convergent cone with an opening angle = 60°	35
Figure 10.7 - Permissible value v_{15K} pS for convergent cone with an opening angle = 70°	36
Figure 10.8 - Permissible value v_{15K} pS for convergent cone (corner joint) with an opening angle = 10° to 70°	37
Figure 11 -- Opening factor CA for flat ends and plates without additional marginal moment	38
Figure 12 - Design factors for unstayed circular flat ends and plates	40
Figure 13 -- Design factor CE for rectangular or elliptical flat plates	41
Figure 14 -- Increased thickness of a cylindrical shell	42
Figure 15 -- Increased thickness of a conical shell	42
Figure 16 -- Set-on reinforcement ring	42
Figure 17 -- Set-in reinforcement ring	42
Figure 18 -- Pad reinforcement	43
Figure 19 -- Nozzle reinforcement	43
Figure 20 -- Necked out opening	43
Figure 21 -- Pad	44
Figure 22 -- Calculation scheme for cylindrical shells	44
Figure 23 -- Calculation scheme for spherical shells	45
Figure 24 -- Calculation scheme for adjacent nozzles or in a longitudinal direction of a cylinder	45
Figure 25 -- Openings between longitudinal and circumferential direction	46
Figure 26 -- Calculation scheme for adjacent nozzles in a sphere or in a circumferential direction of a cylinder	46
Figure 27 a) -- Seams which do not require a taper	50
Figure 27 b) -- Seams which do require a taper	50
Figure 27 -- Plate alignment	50
Figure 28 -- Gauge details	52
Figure A.1 -- Stress categories and limits of stress intensity	68
Figure A.2 -- For vessels not subject to external pressure	69
Figure C.1 -- Stress/strain curve for carbon steel	79
Figure C.2 -- Stress/strain curve for austenitic stainless steel	79
Figure D.1 -- Examples of relief systems	84
Figure E.1 -- Joggle joint	86
Figure E.2 -- Intermediate end	87

Figure E.3 -- Backing strip	87
Figure E.4 -- End plate closure (examples)	88
Figure E.5 -- Non full penetration nozzle welds	88