

# ISO 4249-3:2010-11 (E)

## Motorcycle tyres and rims (code-designated series) - Part 3: Rims

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Finish .....</b>	<b>1</b>
<b>3.1</b>	<b>Rim contour .....</b>	<b>1</b>
<b>3.2</b>	<b>Rim valve hole .....</b>	<b>1</b>
<b>4</b>	<b>Designation .....</b>	<b>3</b>
<b>5</b>	<b>Cylindrical bead seat .....</b>	<b>3</b>
<b>5.1</b>	<b>Rim contours .....</b>	<b>3</b>
<b>5.2</b>	<b>Rim diameters .....</b>	<b>4</b>
<b>6</b>	<b>Tapered bead seat rims (MT type) .....</b>	<b>4</b>
<b>6.1</b>	<b>Rim contours .....</b>	<b>4</b>
<b>6.2</b>	<b>Bead seat contours .....</b>	<b>6</b>
<b>6.3</b>	<b>Rim diameter and hump circumference .....</b>	<b>7</b>
<b>7</b>	<b>Permitted rim widths .....</b>	<b>7</b>
<b>Annex A (informative) Rim circumference measurement -- Tapered bead seat (MT type) rims .....</b>		<b>9</b>
<b>Bibliography .....</b>		<b>11</b>