

ISO 14890:2013-02 (E)

Conveyor belts - Specification for rubber- or plastics-covered conveyor belts of textile construction for general use

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Designation	2
4.1	Belting designation	2
4.2	Examples for ordering	3
5	Construction	4
6	Length	5
7	Width	5
8	Rubber cover	6
9	Tolerances on total belt thickness and cover thickness	7
9.1	Tolerance on total belt thickness	7
9.2	Tolerance on cover thickness	7
10	Transverse fabric joints in multi-ply belting	7
10.1	General	7
10.2	Outer plies	7
10.3	Inner plies	8
10.4	Adjacent plies and non-adjacent plies	8
10.5	Joints in the same ply	8
10.6	Mono-ply, duo-ply and solid woven belting	8
11	Longitudinal fabric joints in multi-ply belting and duo-ply belting	8
11.1	Spacing of joints	8
11.2	Number of joints	8
12	Longitudinal fabric or carcass joints in solid woven and mono-ply belting	8
13	Elongation	8
14	Full thickness tensile strength	8
15	Adhesion	9
16	Troughability	9
17	Sampling	10
18	Identification	10

Annex A (informative) Items to be agreed between the manufacturer and purchaser	11
Annex B (informative) Helpful information to be supplied by the purchaser	12
Annex C (informative) Lateral drift -- Straight running	14
Bibliography	15