

# ISO 4000-1:2013-02 (E)

## Passenger car tyres and rims - Part 1: Tyres (metric series)

---

| <b>Contents</b>   |  | <b>Page</b> |
|---|--|-------------|
| Foreword .....  |  | iv          |
| <b>1</b>  | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>  | <b>Normative references .....</b>  | <b>1</b>    |
| <b>3</b>  | <b>Terms and definitions .....</b>   | <b>1</b>    |
| <b>4</b>  | <b>Designation .....</b>   | <b>1</b>    |
| <b>4.1</b>  | <b>Size and construction .....</b>   | <b>1</b>    |
| <b>4.2</b>  | <b>Service description .....</b>   | <b>3</b>    |
| <b>4.3</b>  | <b>Other service characteristics .....</b>   | <b>4</b>    |
| <b>5</b>  | <b>Marking .....</b>   | <b>6</b>    |
| <b>6</b>  | <b>Tyre dimensions .....</b>   | <b>7</b>    |
| <b>6.1</b>  | <b>Rounding values .....</b>   | <b>7</b>    |
| <b>6.2</b>  | <b>Calculation of design tyre dimensions .....</b>   | <b>7</b>    |
| <b>6.3</b>  | <b>Calculation of maximum overall (grown) tyre dimensions in service tyres mounted on their measuring rims .....</b> | <b>8</b>    |
| <b>6.4</b>  | <b>Calculation of minimum tyre dimensions for radial-ply tyres mounted on their measuring rims .....</b>             | <b>9</b>    |
| <b>6.5</b>  | <b>Range of approved rims .....</b>  | <b>9</b>    |
| <b>7</b>  | <b>Tyre dimension measurement procedure .....</b>  | <b>10</b>   |
| <b>8</b>  | <b>Inflation pressures .....</b>   | <b>10</b>   |
| <b>9</b>  | <b>Load capacities .....</b>   | <b>11</b>   |
| <b>10</b>   | <b>Choice of tyre sizes .....</b>  | <b>11</b>   |
| <b>11</b>   | <b>Camber angle .....</b>  | <b>12</b>   |
| <b>Annex A (normative) Guideline values for metric-series tyres .....</b>         |  | <b>14</b>   |
| <b>Annex B (normative) Load indices for passenger car tyres .....</b>             |  | <b>23</b>   |
| <b>Annex C (normative) Minimum inflation pressure for intermediate load .....</b> |  | <b>45</b>   |
| <b>Annex D (informative) Other existing size markings .....</b>                   |  | <b>53</b>   |
| <b>Bibliography .....</b>   |  | <b>55</b>   |