ISO 23671:2015-09 (E)

Passenger car tyres - Method for measuring relative wet grip performance - Loaded new tyres

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Methods for measuring wet grip 2

5 General test conditions 2
5.1 Track characteristics 2
5.2 Wetting conditions 3
5.3 Atmospheric conditions 4
5.4 Reference tyre 4

6 Measurement of tyre wet grip on a standard vehicle 4
6.1 Principle 4
6.2 Equipment 4
6.2.1 Vehicle 4
6.2.2 Measuring equipment 4
6.3 Conditioning of the test track 5
6.4 Test speed measurement requirements 5
6.5 Tyres and rims 5
6.5.1 Tyre preparation and break-in 5
6.5.2 Tyre load 5
6.5.3 Tyre inflation pressure 5
6.6 Procedure 5
6.7 Processing of measurement results 6
6.7.1 Calculation of the average deceleration, AD 6
6.7.2 Validation of results 6
6.7.3 Calculation of average, AD 7
6.7.4 Calculation of braking force coefficient, BFC 7
6.7.5 Calculation of the relative wet grip performance index of the tyre 7
6.8 Wet grip performance comparison between a candidate tyre and a reference tyre using a control tyre 8
6.8.1 General 8
6.8.2 Principle of the approach 8
6.8.3 Selection of a control tyre set 9
6.8.4 Storage and preservation 9
6.8.5 Replacement of control tyres 9

7 Test method using a trailer or a tyre test vehicle 9
7.1 Principle 9
7.2 Test apparatus 9
7.3 Selection and preparation of test tyres 11
7.4 Preparation of apparatus and test track 11
7.4.1 Towed trailer 11
7.4.2 Tyre test vehicle 12
7.4.3 Instrumentation and equipment 12
7.4.4 Conditioning of the track 12

7.5 General test conditions 12
7.6 Procedure 12
7.7 Processing of measurement results 13

Annex A (informative) Example test report of wet grip index 15

Bibliography 18