

ISO 23671:2015-09 (E)

Passenger car tyres - Method for measuring relative wet grip performance - Loaded new tyres

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Methods for measuring wet grip	2
5	General test conditions	2
5.1	Track characteristics	2
5.2	Wetting conditions	3
5.3	Atmospheric conditions	4
5.4	Reference tyre	4
6	Measurement of tyre wet grip on a standard vehicle	4
6.1	Principle	4
6.2	Equipment	4
6.2.1	Vehicle	4
6.2.2	Measuring equipment	4
6.3	Conditioning of the test track	5
6.4	Test speed measurement requirements	5
6.5	Tyres and rims	5
6.5.1	Tyre preparation and break-in	5
6.5.2	Tyre load	5
6.5.3	Tyre inflation pressure	5
6.6	Procedure	5
6.7	Processing of measurement results	6
6.7.1	Calculation of the average deceleration, AD	6
6.7.2	Validation of results	6
6.7.3	Calculation of average, AD	7
6.7.4	Calculation of braking force coefficient, BFC	7
6.7.5	Calculation of the relative wet grip performance index of the tyre	7
6.8	Wet grip performance comparison between a candidate tyre and a reference tyre using a control tyre	8
6.8.1	General	8
6.8.2	Principle of the approach	8
6.8.3	Selection of a control tyre set	9
6.8.4	Storage and preservation	9
6.8.5	Replacement of control tyres	9
7	Test method using a trailer or a tyre test vehicle	9
7.1	Principle	9
7.2	Test apparatus	9
7.3	Selection and preparation of test tyres	11
7.4	Preparation of apparatus and test track	11
7.4.1	Towed trailer	11
7.4.2	Tyre test vehicle	12
7.4.3	Instrumentation and equipment	12
7.4.4	Conditioning of the track	12

7.5	General test conditions	12
7.6	Procedure	12
7.7	Processing of measurement results	13
Annex A (informative) Example test report of wet grip index		15
Bibliography		18