

ISO 4000-1:2015-09 (E)

Passenger car tyres and rims - Part 1: Tyres (metric series)

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Designation	1
4.1	Size and construction	1
4.1.1	Characteristics	1
4.1.2	Nominal section width	1
4.1.3	Nominal aspect ratio	2
4.1.4	Tyre construction code	2
4.1.5	Nominal rim diameter code	2
4.2	Service description	3
4.2.1	General	3
4.2.2	Load index	3
4.2.3	Speed categories	3
4.3	Other service characteristics	3
5	Marking	6
6	Tyre dimensions	7
6.1	Rounding values	7
6.2	Calculation of design tyre dimensions	7
6.2.1	Theoretical rim width, R_{th}	7
6.2.2	Measuring rim width code, R_{mc}	7
6.2.3	Design tyre section width, S	8
6.2.4	Design tyre section height, H	8
6.2.5	Design tyre overall diameter, D_o	8
6.2.6	Guidelines	8
6.3	Calculation of maximum overall (grown) tyre dimensions in service tyres mounted on their measuring rims	8
6.3.1	General	8
6.3.2	Maximum overall (grown) width in service, W_{max}	9
6.3.3	Maximum overall (grown) diameter in service, $D_{o\ max}$	9
6.4	Calculation of minimum tyre dimensions for radial ply tyres mounted on their measuring rims	9
6.4.1	Minimum tyre section width, S_{min}	9
6.4.2	Minimum tyre overall diameter, $D_{o\ min}$	9
6.5	Range of approved rims	10
7	Tyre dimension measurement procedure	10
8	Inflation pressures	10
9	Load capacities	11
10	Choice of tyre sizes	11
11	Camber angle	12

Annex A (normative) Guideline values for metric-series tyres	14
Annex B (normative) Load indices for passenger car tyres	21
Annex C (normative) Minimum inflation pressure for intermediate load	43
Annex D (informative) Other existing size markings	51
Bibliography	53