

DIN EN 1762:2017-06 (E)

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specification

Contents		Page
European foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Classification	6
5	Materials and construction	7
5.1	Hose	7
5.2	Hose assemblies	7
6	Dimensions	7
6.1	Nominal bore, internal diameters, outside diameters, tolerances, and minimum bend radius	7
Table 1 -- Dimensions and tolerances of hoses of types D and D-LT		8
Table 2 -- Dimensions and tolerances of hoses of types SD, SD-LTS and SD-LTR		9
6.2	Minimum thickness of lining and cover	9
6.3	Concentricity	9
6.4	Tolerances on length	9
7	Physical properties	10
7.1	Rubber Compounds	10
Table 3 -- Physical properties of compounds		10
7.2	Finished hose and hose assemblies	11
Table 4 -- Physical properties of finished hose and hose assemblies		11
8	Electrical properties	12
8.1	General	12
8.2	Textile reinforced hoses with bonding wires	12
8.3	Textile reinforced hoses with conducting materials	13
8.4	Wire helix reinforced hoses	13
8.4.1	Grade M-hoses (see 8.2)	13
8.4.2	Grade -hoses (see 8.3)	13
8.5	Hose assemblies that are required to be discontinuous	13
9	Type testing	13
10	Frequency of testing	13
11	Marking	14
11.1	Hoses	14
11.2	Hose assemblies	14
Annex A (normative) Flammability test		15

A.1	Method	15
A.2	Assessment	15
Figure A.1 -- Arrangement for flammability test		16
Annex B (normative) Test frequency		17
Table B.1 -- Type and routine tests		17
Annex C (informative) Test frequency		19
Table C.1 -- Recommended test frequency (Production acceptance tests)		19