

# ISO 29802:2017-06 (E)

## All-terrain (AT) tyres and rims - Symbol marked pneumatic tyres on 5 degree tapered rims - Designation, dimension, marking and load ratings

---

| <b>Contents</b> |   | <b>Page</b> |
|-----------------|---|-------------|
| Foreword .....  |   | v           |
| 1               | Scope .....   | 1           |
| 2               | Normative references .....  | 1           |
| 3               | Terms and definitions .....   | 1           |
| 4               | Tyre size designations .....  | 2           |
| 4.1             | Dimensional and constructional characteristics .....                | 2           |
| 4.1.1           | General .....   | 2           |
| 4.1.2           | Prefix .....  | 2           |
| 4.1.3           | Nominal overall diameter code .....                                 | 2           |
| 4.1.4           | Nominal section width code .....                                    | 2           |
| 4.1.5           | Tyre construction code .....  | 3           |
| 4.1.6           | Nominal rim diameter code .....                                     | 3           |
| 4.2             | Service condition .....   | 3           |
| 4.2.1           | General .....   | 3           |
| 4.2.2           | Symbol of reference inflation pressure .....                        | 4           |
| 4.2.3           | Service description .....   | 4           |
| 4.3             | Other service characteristics .....                                 | 4           |
| 5               | Marking .....   | 4           |
| 6               | Tyre dimensions .....   | 5           |
| 6.1             | General .....   | 5           |
| 6.2             | Calculation of design tyre dimensions .....                         | 5           |
| 6.2.1           | Theoretical rim width, $R_{th}$ .....                               | 5           |
| 6.2.2           | Measuring rim width, $R_m$ .....                                    | 5           |
| 6.2.3           | Design tyre section width, $S$ .....                                | 5           |
| 6.2.4           | Design tyre overall diameter, $D_o$ .....                           | 6           |
| 6.2.5           | Design tyre section height, $H$ .....                               | 6           |
| 6.3             | Calculation of "maximum overall tyre dimensions" .....              | 6           |
| 6.3.1           | General .....   | 6           |
| 6.3.2           | Maximum tyre overall width, $W_{max}$ .....                         | 6           |
| 6.3.3           | Maximum tyre overall diameter, $D_{o,max}$ .....                    | 6           |
| 6.4             | Calculation of "maximum overall grown tyre dimensions" .....        | 6           |
| 6.4.1           | General .....   | 6           |
| 6.4.2           | Maximum grown tyre overall width in service, $WG$ .....             | 7           |
| 6.4.3           | Maximum dynamic tyre overall diameter in service, $D_{o,dyn}$ ..... | 7           |
| 6.5             | Calculation of "minimum tyre dimensions" .....                      | 7           |
| 6.5.1           | General .....   | 7           |
| 6.5.2           | Minimum tyre section width, $S_{min}$ .....                         | 7           |
| 6.5.3           | Minimum tyre overall diameter, $D_{o,min}$ .....                    | 7           |
| 6.6             | Range of approved rims widths .....                                 | 7           |
| 7               | Method of measurement of tyre dimensions .....                      | 8           |
| 8               | Reference load carrying capacity .....                              | 8           |
| 9               | Load ratings .....  | 9           |

|             |  |           |
|-------------|--|-----------|
| <b>10</b>   | <b>Inflation pressures .....</b>   | <b>9</b>  |
| <b>11</b>   | <b>Rims .....</b>  | <b>9</b>  |
| <b>11.1</b> | <b>Designation and marking .....</b>                                     | <b>9</b>  |
| <b>11.2</b> | <b>Rim contours .....</b>  | <b>10</b> |
| <b>11.3</b> | <b>Rim diameter and hump circumference .....</b>                         | <b>11</b> |
| <b>12</b>   | <b>Valve hole .....</b>  | <b>11</b> |
| <b>12.1</b> | <b>General .....</b>   | <b>11</b> |
| <b>12.2</b> | <b>Snap-in valves .....</b>  | <b>11</b> |
|             | <b>Annex A (normative) Load indices for all-terrain (AT) tyres .....</b> | <b>13</b> |