

# ISO 29802:2017-06 (E)

## All-terrain (AT) tyres and rims - Symbol marked pneumatic tyres on 5 degree tapered rims - Designation, dimension, marking and load ratings

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Tyre size designations .....	2
4.1	Dimensional and constructional characteristics .....	2
4.1.1	General .....	2
4.1.2	Prefix .....	2
4.1.3	Nominal overall diameter code .....	2
4.1.4	Nominal section width code .....	2
4.1.5	Tyre construction code .....	3
4.1.6	Nominal rim diameter code .....	3
4.2	Service condition .....	3
4.2.1	General .....	3
4.2.2	Symbol of reference inflation pressure .....	4
4.2.3	Service description .....	4
4.3	Other service characteristics .....	4
5	Marking .....	4
6	Tyre dimensions .....	5
6.1	General .....	5
6.2	Calculation of design tyre dimensions .....	5
6.2.1	Theoretical rim width, $R_{th}$ .....	5
6.2.2	Measuring rim width, $R_m$ .....	5
6.2.3	Design tyre section width, $S$ .....	5
6.2.4	Design tyre overall diameter, $D_o$ .....	6
6.2.5	Design tyre section height, $H$ .....	6
6.3	Calculation of "maximum overall tyre dimensions" .....	6
6.3.1	General .....	6
6.3.2	Maximum tyre overall width, $W_{max}$ .....	6
6.3.3	Maximum tyre overall diameter, $D_{o,max}$ .....	6
6.4	Calculation of "maximum overall grown tyre dimensions" .....	6
6.4.1	General .....	6
6.4.2	Maximum grown tyre overall width in service, $WG$ .....	7
6.4.3	Maximum dynamic tyre overall diameter in service, $D_{o,dyn}$ .....	7
6.5	Calculation of "minimum tyre dimensions" .....	7
6.5.1	General .....	7
6.5.2	Minimum tyre section width, $S_{min}$ .....	7
6.5.3	Minimum tyre overall diameter, $D_{o,min}$ .....	7
6.6	Range of approved rims widths .....	7
7	Method of measurement of tyre dimensions .....	8
8	Reference load carrying capacity .....	8
9	Load ratings .....	9

<b>10</b>	<b>Inflation pressures .....</b>	<b>9</b>
<b>11</b>	<b>Rims .....</b>	<b>9</b>
<b>11.1</b>	<b>Designation and marking .....</b>	<b>9</b>
<b>11.2</b>	<b>Rim contours .....</b>	<b>10</b>
<b>11.3</b>	<b>Rim diameter and hump circumference .....</b>	<b>11</b>
<b>12</b>	<b>Valve hole .....</b>	<b>11</b>
<b>12.1</b>	<b>General .....</b>	<b>11</b>
<b>12.2</b>	<b>Snap-in valves .....</b>	<b>11</b>
	<b>Annex A (normative) Load indices for all-terrain (AT) tyres .....</b>	<b>13</b>