

ISO 3862:2017-07 (E)

Rubber hoses and hose assemblies - Rubber-covered spiral-wire-reinforced hydraulic types for oil-based or water-based fluids - Specification

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Classification	2
5	Materials and construction	2
5.1	Hoses	2
5.2	Hose assemblies	2
6	Dimensions	2
6.1	Hose diameters and hose concentricity	2
6.2	Length	5
7	Performance requirements	5
7.1	General	5
7.2	Hydrostatic requirements	5
7.3	Minimum bend radius	6
7.4	Resistance to impulse	7
7.4.1	Resistance to impulse with oil-based fluid	7
7.4.2	Resistance to impulse with water-based fluid	7
7.4.3	Optional impulse test	8
7.5	Leakage of hose assemblies	8
7.6	Cold flexibility	8
7.7	Adhesion between components	8
7.8	Fluid resistance	8
7.8.1	General	8
7.8.2	Oil resistance	8
7.8.3	Water resistance	9
7.9	Ozone resistance	9
7.10	Visual examination	9
8	Marking	9
8.1	Hoses	9
8.2	Hose assemblies	9
Annex A (normative) Type and routine testing of production hoses		11
Annex B (informative) Production acceptance testing		12
Annex C (informative) Recommendations for lengths of supplied hoses and tolerances on lengths of hose assemblies		13