ISO 3862:2017-07 (E)

Rubber hoses and hose assemblies - Rubber-covered spiral-wire-reinforced hydraulic types for oil-based or water-based flui ds - Specification

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Classification 2

5 Materials and construction 2
5.1 Hoses 2
5.2 Hose assemblies 2

6 Dimensions 2
6.1 Hose diameters and hose concentricity 2
6.2 Length 5

7 Performance requirements 5
7.1 General 5
7.2 Hydrostatic requirements 5
7.3 Minimum bend radius 6
7.4 Resistance to impulse 7
7.4.1 Resistance to impulse with oil-based fluid 7
7.4.2 Resistance to impulse with water-based fluid 7
7.4.3 Optional impulse test 8
7.5 Leakage of hose assemblies 8
7.6 Cold flexibility 8
7.7 Adhesion between components 8
7.8 Fluid resistance 8
7.8.1 General 8
7.8.2 Oil resistance 8
7.8.3 Water resistance 9
7.9 Ozone resistance 9
7.10 Visual examination 9

8 Marking 9
8.1 Hoses 9
8.2 Hose assemblies 9

Annex A (normative) Type and routine testing of production hoses 11

Annex B (informative) Production acceptance testing 12

Annex C (informative) Recommendations for lengths of supplied hoses and tolerances on lengths of hose assemblies 13