

ISO 16301:2017-09 (E)

Rubber and plastics hoses and hose assemblies, wire- or textile-reinforced, for manually operated hydraulic jacks - Specification

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	List of significant hazards	2
4.1	General	2
4.2	Hazards due to bursting or leaking of hoses	2
4.3	Hazards due to failure of connectors	3
4.4	Hazards due to errors by the operator	4
4.5	Hazards due to change in length of hose assembly	5
5	Classification	5
5.1	Classes	5
5.2	Grades	5
6	Materials and construction	6
6.1	Hoses	6
6.2	Hose assemblies	6
7	Dimensions and tolerances	6
7.1	Diameters	6
7.2	Cover thickness	6
7.3	Concentricity	6
8	Physical properties	7
8.1	Fluid resistance	7
8.1.1	Test pieces	7
8.1.2	Oil resistance	7
8.2	Performance requirements	7
8.2.1	Hydrostatic requirements	7
8.2.2	Change in length	7
8.2.3	Minimum bend radius	8
8.2.4	Resistance to impulse	8
8.2.5	Leakage of hose assemblies	9
8.2.6	Cold bending test	9
8.2.7	Ozone resistance	9
8.2.8	Electrical conductivity	10
8.2.9	Visual examination	10
9	Frequency of testing	10
10	Marking	10
10.1	Hoses	10
10.2	Hose assemblies	11
11	Test report	11

12	Recommendations for packaging and storage	11
	Annex A (informative) Selection of hoses	12
	Annex B (normative) Test frequency	13
	Annex C (informative) Production tests	14
	Annex D (informative) Recommendations for lengths of supplied hoses and hose assemblies	15
	Annex E (normative) Test method for electrical conductivity	16
	Bibliography	17