

ISO 18804:2017-10 (E)

Rims for agricultural, forestry and construction machines

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Rim diameter and circumferences | 1 |
| 5 | Rim contours and valve holes | 3 |
| 5.1 | Drop-centre W, DW and TW rims | 3 |
| 5.2 | Drop-centre DH rims | 7 |
| 5.3 | Drop-centre MW rims | 9 |
| 5.4 | Drop-centre DD rims | 11 |
| 5.5 | Other drop-centre rims | 11 |
| 5.6 | Semi-drop-centre rims (multi-piece) | 14 |
| 5.7 | Divided rims | 16 |
| 5.8 | 5° and 3° flat base rims (multi-piece) -- DWM, VF and HF | 16 |
| 5.9 | Full tapered bead seat rims (multi-piece) -- TH | 18 |
| 5.10 | AG 15° drop-centre rims | 19 |
| 6 | Rim knurling | 21 |
| Annex A (normative) Rim diameter measurements | | 22 |
| Annex B (informative) 5° drop-centre rims with nominal diameter codes 15.3 and 16.1 | | 24 |
| Annex C (informative) 15° drop-centre rims with nominal diameter code 15.5, 16.5, and 17.5 | | 26 |
| Bibliography | | 28 |