

ISO 28017:2018-02 (E)

Rubber hoses and hose assemblies, wire or textile reinforced, for dredging applications - Specification

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Classification	2
4.1	Classes	2
4.2	Grades	2
5	Materials and construction	3
5.1	Hoses	3
5.2	Flotation material	3
5.3	End fittings and end connections	4
6	Dimension and tolerances	4
6.1	Diameters	4
6.2	Hose assembly length	5
7	Physical properties	5
7.1	Rubber compounds	5
7.1.1	Abrasion resistance of lining	5
7.1.2	Tear strength of lining	5
7.1.3	Rebound resilience of lining	5
7.1.4	Ozone resistance of cover	5
7.2	Performance requirements	6
7.2.1	Hydrostatic requirements	6
7.2.2	Change in length	6
7.2.3	Bending test	7
7.2.4	Leakage of hose assemblies (proof pressure test)	7
7.2.5	Minimum reserve buoyancy	7
7.2.6	Flotation material recovery	8
7.2.7	Adhesion between components	8
7.2.8	Adhesion between end fitting and lining	8
7.2.9	Minimum tensile strength of empty hose assemblies	9
7.2.10	Vacuum resistance	9
7.2.11	Dimensions of flange and other connections	9
7.2.12	Visual examination	9
7.3	Frequency of testing	9
8	Test certificate or report	10
9	Marking	10
10	Recommendations for packaging and storage	10
Annex A (normative) Type tests and routine tests		11
Annex B (normative) Measurement of adhesion between end fitting and lining		12

Annex C (normative) Hose assembly tensile-strength test	15
Bibliography	18