

ISO 28580:2018 (E)

Passenger car, truck and bus tyre rolling resistance measurement method — Single point test and correlation of measurement results

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Test methods
5	Test equipment
5.1	General
5.2	Drum specifications
5.2.1	Diameter
5.2.2	Surface
5.2.3	Width
5.3	Measuring rim
5.4	Load, alignment, control and instrumentation accuracies
5.5	Thermal environment
5.5.1	Reference conditions
5.5.2	Alternative conditions
6	Test conditions
6.1	General
6.2	Test speeds
6.3	Test load
6.4	Test inflation pressure
6.5	Duration and speed
7	Test procedure
7.1	General
7.2	Thermal conditioning
7.3	Pressure adjustment
7.4	Warm-up
7.5	Measurement and recording
7.6	Measurement of parasitic losses
7.6.1	General
7.6.2	Skim test reading
7.6.3	Deceleration method
7.7	Allowance for machines exceeding σ_m criterion
8	Data interpretation
8.1	Determination of parasitic losses
8.1.1	General
8.1.2	Force method at tyre spindle
8.1.3	Torque method at drum axis
8.1.4	Power method at drum axis
8.1.5	Deceleration method
8.2	Rolling resistance calculation
8.2.1	General
8.2.2	Force method at tyre spindle
8.2.3	Torque method at drum axis
8.2.4	Power method at drum axis

8.2.5	Deceleration method
9	Data analysis
9.1	Rolling resistance coefficient
9.2	Temperature correction
9.3	Drum diameter correction
9.4	Measurement result
10	Measurement machines alignment and monitoring requirements
10.1	General
10.2	Conditions for reference machine
10.3	Conditions for candidate machine
10.4	Alignment tyre requirements
10.5	Alignment procedure
Annex A (normative) Test equipment tolerances	
A.1	Purpose
A.2	Alignment
A.2.1	General
A.2.2	Load application
A.2.3	Tyre alignment
A.2.3.1	Camber angle
A.2.3.2	Slip angle
A.3	Control accuracy
A.4	Instrumentation accuracy
A.5	Compensation for load/spindle force interaction and load misalignment for force method only
A.6	Test surface roughness
Annex B (informative) Measurement methods of moment of inertia for drum and tyre assembly — Deceleration method	
B.1	Limitation
B.2	Test drum inertia
B.2.1	Measurement method
B.2.1.1	Equipment needed
B.2.1.2	Test arrangement
B.2.1.3	Theory
B.2.1.4	Method
B.2.2	Determination method
B.3	Tyre assembly inertia
B.3.1	Spring method
B.3.1.1	Equipment needed
B.3.1.2	Theory
B.3.1.3	Method
B.3.2	Bifilar pendulum (rope) method
B.3.2.1	General
B.3.2.2	Theory
B.3.2.3	Method
Annex C (informative) Test rim runout	
Annex D (informative) Publications of tyre standards organizations	
Annex E (informative) Example for larger truck bus warm-up duration	
Annex F (informative) Example for machine drift evaluation	
F.1	General
F.2	Concept of a moving average
F.3	Application of the concept
F.3.1	General
F.3.2	Laboratory with two or more machines
F.3.3	Laboratory with only one machine or a single physical reference machine