

ISO 8664:2018 (E)

Tyres for agricultural tractors and machines — Code-designated and service-description marked radial drive-wheel tyres

Contents

| | |
|---------|---|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Tyre marking |
| 4.1 | General |
| 4.2 | Supplementary service description |
| 4.3 | Additional information |
| 4.4 | Tyre classification and nomenclature |
| 4.5 | Tyre maximum pressure for bead seating pictogram |
| 5 | Tyre dimensions |
| 6 | Tyre load ratings |
| 7 | Tyre applications other than at reference speed |
| 7.1 | General |
| 7.2 | Field applications with high and sustained torque |
| 7.3 | Tyres marked with additional service description |
| 8 | Tyre application on combine harvesters |
| 9 | Tyre parameters for vehicle speed reference |
| Annex A | (normative) Tyre size designations, measurement rims and tyre dimensions |
| Annex B | (normative) Load index and basic tyre load with reference inflation pressures 120 kPa, 160 kPa, 210 kPa and 250 kPa |
| Annex C | (normative) Approved rim contours |
| Annex D | (normative) Rolling circumference (RC), rolling circumference index (RCI) and speed radius index (SRI) |

Page count: 14