

DIN EN 1762:2019-03 (E)

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specification

Contents		Page
European foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	5
4	Classification	5
5	Materials and construction	6
5.1	Hose	6
5.2	Hose assemblies	6
6	Dimensions	6
6.1	Nominal bore, internal diameters, outside diameters, tolerances, and minimum bend radius	6
6.2	Minimum thickness of lining and cover	8
6.3	Concentricity	8
6.4	Tolerances on length	8
7	Physical properties	9
7.1	Rubber compounds	9
7.2	Finished hose and hose assemblies	10
8	Electrical properties	11
8.1	General	11
8.2	Textile reinforced hoses with bonding wires	12
8.3	Textile reinforced hoses with conducting materials	12
8.4	Wire helix reinforced hoses	12
8.4.1	Grade M-hoses (see 8.2)	12
8.4.2	Grade -hoses (see 8.3)	12
8.5	Hose assemblies that are required to be discontinuous	12
9	Type testing	12
10	Frequency of testing	13
11	Marking	13
11.1	Hoses	13
11.2	Hose assemblies	13
Annex A (normative) Flammability test		14
A.1	Method	14
A.2	Assessment	14
Annex B (normative) Test frequency for type tests and routine tests		16
Annex C (informative) Test frequency for production acceptance tests		18

Annex D (informative) Environmental checklist	20
Bibliography	22