DIN EN 1762:2019-03 (E)

Rubber hoses and hose assemblies for liquefied petroleum gas, LPG (liquid or gaseous phase), and natural gas up to 25 bar (2,5 MPa) - Specif ication

Contents

Page

European foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 5

4 Classification 5

5 Materials and construction 6
5.1 Hose 6
5.2 Hose assemblies 6

6 Dimensions 6
6.1 Nominal bore, internal diameters, outside diameters, tolerances, and minimum bend radius 6
6.2 Minimum thickness of lining and cover 8
6.3 Concentricity 8
6.4 Tolerances on length 8

7 Physical properties 9
7.1 Rubber compounds 9
7.2 Finished hose and hose assemblies 10

8 Electrical properties 11
8.1 General 11
8.2 Textile reinforced hoses with bonding wires 12
8.3 Textile reinforced hoses with conducting materials 12
8.4 Wire helix reinforced hoses 12
8.4.1 Grade M-hoses (see 8.2) 12
8.4.2 Grade -hoses (see 8.3) 12
8.5 Hose assemblies that are required to be discontinuous 12

9 Type testing 12

10 Frequency of testing 13

11 Marking 13
11.1 Hoses 13
11.2 Hose assemblies 13

Annex A (normative) Flammability test 14

A.1 Method 14
A.2 Assessment 14

Annex B (normative) Test frequency for type tests and routine tests 16

Annex C (informative) Test frequency for production acceptance tests 18

Annex D (informative) Environmental checklist 20

Bibliography 22