

# ISO 11425:2018 (E)

## Rubber hoses and hose assemblies for automobile power-steering systems — Specification

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
| 1       | Scope   |
| 2       | Normative references  |
| 3       | Terms and definitions   |
| 4       | Types of hose   |
| 5       | Construction and materials  |
| 6       | Dimensions and tolerances   |
| 7       | Performance requirement   |
| 7.1     | Impulse resistance  |
| 7.2     | Burst pressure requirement  |
| 7.3     | Change in length  |
| 7.4     | Low-temperature flexibility   |
| 7.5     | Adhesion  |
| 7.6     | Ozone resistance  |
| 7.7     | Volumetric expansion  |
| 7.8     | Contamination   |
| 7.9     | Corrosion of end fittings   |
| 7.10    | Proof pressure requirement  |
| 7.11    | Cold-start requirement (type approval test for type 4 hose assemblies only) |
| 7.11.1  | Requirement   |
| 7.11.2  | Test method   |
| 7.12    | Low-pressure burst pressure requirement (type 4 hose assemblies only)       |
| 8       | Marking   |
| Annex A | (normative) Method of test for volumetric expansion                         |
| A.1     | Principle   |
| A.2     | Apparatus   |
| A.3     | Test fluid  |
| A.4     | Test piece  |
| A.5     | Procedure   |
| A.6     | Expression of results   |
| A.7     | Test report   |
| Annex B | (normative) Method of test for contamination                                |
| B.1     | Principle   |
| B.2     | Reagent   |
| B.3     | Apparatus   |
| B.4     | Procedure   |
| B.5     | Expression of results   |
| B.6     | Test report   |
| Annex C | (informative) Typical outside-diameter ranges                               |