

# DIN 7863-1:2019-12 (E)

## Elastomer glazing and panel gaskets for windows and claddings - Technical delivery conditions - Part 1: Non cellular elastomer glazing and panel gaskets

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b> <b>Scope</b> .....		<b>4</b>
<b>2</b> <b>Normative references</b> .....		<b>4</b>
<b>3</b> <b>Terms and definitions</b> .....		<b>5</b>
<b>4</b> <b>Shape and dimensions</b> .....		<b>5</b>
<b>5</b> <b>Material</b> .....		<b>5</b>
5.1 <b>General</b> .....		<b>5</b>
5.2 <b>Temperature classes</b> .....		<b>5</b>
5.3 <b>Material classes</b> .....		<b>6</b>
<b>6</b> <b>Requirements</b> .....		<b>6</b>
6.1 <b>Material requirements</b> .....		<b>6</b>
6.2 <b>Compatibility with contact media</b> .....		<b>9</b>
<b>7</b> <b>Test methods</b> .....		<b>9</b>
7.1 <b>General</b> .....		<b>9</b>
7.2 <b>Hardness and tolerance on hardness</b> .....		<b>9</b>
7.3 <b>Tensile strength and elongation at break</b> .....		<b>9</b>
7.4 <b>Compression set at 100 °C</b> .....		<b>9</b>
7.5 <b>Compression set at 70 °C</b> .....		<b>9</b>
7.6 <b>Compression set at –25 °C</b> .....		<b>9</b>
7.7 <b>Thermal ageing</b> .....		<b>9</b>
7.7.1 <b>Temperature class –25 °C to +70 °C</b> .....		<b>9</b>
7.7.2 <b>Temperature class –25 °C to +100 °C</b> .....		<b>9</b>
7.8 <b>Low temperature performance</b> .....		<b>9</b>
7.9 <b>Resistance to ozone</b> .....		<b>10</b>
7.10 <b>Compatibility with contact media</b> .....		<b>10</b>
7.11 <b>Reaction to fire</b> .....		<b>10</b>
<b>8</b> <b>Test report</b> .....		<b>10</b>
<b>Bibliography</b> .....		<b>11</b>