ISO 18807:2019-08 (E)

Tyres and rims for logging and forestry service

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Marking 1
4.1 General 1
4.2 Tyre size designation 2
4.2.1 Conventional code designated diagonal tyres 2
4.2.2 3-part code designated diagonal tyres 2
4.2.3 Metric designated tyres 2
4.3 Load rating 2
4.3.1 Conventional and 3-part code designated diagonal sizes 2
4.3.2 Metric sizes 2
4.4 Additional markings 3

5 Tyre dimensions 3
5.1 General 3
5.2 Design new tyre dimensions 3
5.2.1 General 3
5.2.2 Section width 3
5.2.3 Overall diameter 4
5.3 Tyre dimensions in service 4

6 Tyre load capacities 4
6.1 General 4
6.2 Conventional code designated diagonal tyres 4
6.2.1 General 4
6.2.2 Transport service and low torque operations 5
6.2.3 Skidder service: operations including high and sustained torque 5
6.2.4 Load and carry 5
6.3 3-part code designated diagonal tyres 5
6.4 Metric designated tyres 5
6.4.1 General 5
6.4.2 Transport service and low torque operations 5
6.4.3 Skidder service 5

7 Rim coordination 5

8 Tubes 6

9 Tyre parameters for vehicle speed reference 6

Annex A (informative) Size designation, measuring rim width code, measurements (section width and overall diameter) for design new tyre and tyre in service 7

Annex B (informative)Basictyreloads(BTL)andinflationpressure(IP) 10

Annex C (informative) Approved rim contours for forestry tyres 15

Annex D (informative) Speed radius index (SRI) 17

Bibliography 19