

ISO 18807:2019-08 (E)

Tyres and rims for logging and forestry service

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Marking	1
4.1	General	1
4.2	Tyre size designation	2
4.2.1	Conventional code designated diagonal tyres	2
4.2.2	3-part code designated diagonal tyres	2
4.2.3	Metric designated tyres	2
4.3	Load rating	2
4.3.1	Conventional and 3-part code designated diagonal sizes	2
4.3.2	Metric sizes	2
4.4	Additional markings	3
5	Tyre dimensions	3
5.1	General	3
5.2	Design new tyre dimensions	3
5.2.1	General	3
5.2.2	Section width	3
5.2.3	Overall diameter	4
5.3	Tyre dimensions in service	4
6	Tyre load capacities	4
6.1	General	4
6.2	Conventional code designated diagonal tyres	4
6.2.1	General	4
6.2.2	Transport service and low torque operations	5
6.2.3	Skidder service: operations including high and sustained torque	5
6.2.4	Load and carry	5
6.3	3-part code designated diagonal tyres	5
6.4	Metric designated tyres	5
6.4.1	General	5
6.4.2	Transport service and low torque operations	5
6.4.3	Skidder service	5
7	Rim coordination	5
8	Tubes	6
9	Tyre parameters for vehicle speed reference	6
Annex A (informative)	Size designation, measuring rim width code, measurements (section width and overall diameter) for design new tyre and tyre in service	7
Annex B (informative)	Basic tyre loads (BTL) and inflation pressure (IP)	10
Annex C (informative)	Approved rim contours for forestry tyres	15

Annex D (informative) Speed radius index (SRI)	17
Bibliography	19