DIN 22102-3:2020-12 (E)

Conveyor belts with textile plies for bulk goods - Part 3: Permanent joints

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms, definitions and symbols 4

4 Dimensions, design and designation 4
4.1 General 4
4.2 Splices for conveyor belts with one textile ply, for belt types 500/1 5
4.3 Splices for conveyor belts with one ply (finger splice), for belt types 630/1 6
4.4 Splices for conveyor belts with two plies and intermediate tension member 7
4.5 Splices for conveyor belts with two or more plies and bonding layers 8

5 Splicing conveyor belts 12
5.1 General 12
5.2 Hot plates in vulcanizing machines 12

6 Electrical and flammability safety requirements 12

7 Marking 12

Figures Figure 1 -- Overlapping splice 5

Figure 2 -- Finger splice 6

Figure 3 -- Splice with intermediate tension member 7

Figure 4 -- Stepped splice 8

Figure 5 -- Conveyor belt with two plies: 1-step splice 9

Figure 6 -- Conveyor belt with two plies: 2-step splice 9

Figure 7 -- Conveyor belt with three plies: 2-step splice 9

Figure 8 -- Conveyor belt with four plies: 3-step splice 10

Figure 9 -- Conveyor belt with five plies: 4-step splice 10

Tables Table 1 -- Loss in breaking strength 5

Table 2 -- Minimum step lengths and splice lengths for overlapping splices 5

Table 3 -- Finger splice dimensions 6

Table 4 -- Minimum steps and splice lengths for splices with intermediate tension member 8

Table 5 -- Minimum steps and splice lengths for conveyor belts with two plies 11

Table 6 -- Minimum steps and splice lengths for conveyor belts with more than two plies 11