

# ISO 5775-2:2021 (E)

## Bicycle tyres and rims — Part 2: Rims

---

### Contents

|         |  |
|---------|--|
|         | Foreword   |
| 1       | Scope  |
| 2       | Normative references   |
| 3       | Terms and definitions  |
| 4       | Symbols and abbreviated terms  |
| 5       | General requirements   |
| 5.1     | Rim contour  |
| 5.2     | Rim valve hole   |
| 5.3     | Rim base protection  |
| 5.4     | Other requirements   |
| 6       | Straight-side type rims  |
| 6.1     | Rim profile  |
| 6.2     | Rim diameters  |
| 6.3     | Designation and marking  |
| 7       | Tubeless straight-side type rims   |
| 7.1     | Rim profile  |
| 7.2     | Rim diameters  |
| 7.3     | Designation and marking  |
| 8       | Hooked bead rims   |
| 8.1     | Rim profile  |
| 8.2     | Rim diameters and circumferences   |
| 8.3     | Designation and marking  |
| 9       | Crotchet type rims   |
| 9.1     | Rim profile  |
| 9.2     | Rim diameters  |
| 9.3     | Designation and marking  |
| 10      | Tubeless crotchet type rims  |
| 10.1    | Rim profile  |
| 10.2    | Rim diameters  |
| 10.3    | Designation and marking  |
| Annex A | (informative) Methods for measuring and gauging bicycle rim dimensions           |
| A.1     | Purpose  |
| A.2     | General  |
| A.3     | Main rim dimensions to be measured and gauged                                    |
| A.4     | Methods for measuring bead seat circumference and calculating bead seat diameter |
| A.4.1   | Method 1   |
| A.4.1.1 | Procedure  |
| A.4.1.2 | Measuring tape details   |
| A.4.2   | Method 2   |
| A.4.2.1 | Procedure  |