

# ISO 22762-5:2021 (E)

## Elastomeric seismic-protection isolators — Part 5: Sliding seismic-protection isolators for buildings

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Classification
5.1	Isolator types
5.2	Classification by sliding friction coefficient
5.3	Cross-section of isolator
6	Requirements
6.1	General
6.2	Type tests and routine tests
6.3	Functional requirements
6.4	Design compressive force and design horizontal velocity
6.5	Performance requirements
6.5.1	General
6.5.2	Tolerance on properties
6.6	Rubber material
6.6.1	Requirements
6.7	Sliding material
6.7.1	Requirements
6.7.2	Sliding materials tests
6.7.2.1	Tensile property tests
6.7.2.2	Hardness test
6.8	Requirements on steel used for flanges, connecting flanges, key plates, steel plates, backing plates, sliding plates and base plates
7	Isolator tests
7.1	General
7.2	Compression, shear stiffness and friction coefficient tests
7.2.1	Compression properties
7.2.2	Compressive-shear test
7.2.2.1	Principle
7.2.2.2	Test machine
7.2.2.2.1	General
7.2.2.2.2	Force correction
7.2.2.3	Test piece
7.2.2.4	Test conditions
7.2.2.4.1	Test temperature
7.2.2.4.2	Conditioning time for test piece
7.2.2.4.3	Compressive force
7.2.2.4.4	Test shear displacement amplitude
7.2.2.4.5	Input wave
7.2.2.4.6	Test vibration velocity
7.2.2.5	Procedure

- 7.2.2.5.1 Attachment of a test piece
- 7.2.2.5.2 Loading
- 7.2.2.6 Expression of results
- 7.2.2.7 Test report
- 7.3 Various dependence tests
  - 7.3.1 Compressive force dependence of shear properties
    - 7.3.1.1 Principle
    - 7.3.1.2 Test machine
      - 7.3.1.2.1 General
      - 7.3.1.2.2 Force correction
    - 7.3.1.3 Test piece
    - 7.3.1.4 Test conditions
      - 7.3.1.4.1 Test temperature
      - 7.3.1.4.2 Conditioning time for test piece
      - 7.3.1.4.3 Compressive force
      - 7.3.1.4.4 Test shear displacement amplitude
      - 7.3.1.4.5 Input wave
      - 7.3.1.4.6 Test vibration velocity
    - 7.3.1.5 Procedure
      - 7.3.1.5.1 Attachment of a test piece
      - 7.3.1.5.2 Loading of test piece
    - 7.3.1.6 Expression of results
    - 7.3.1.7 Test report
  - 7.3.2 Velocity dependence of shear properties
    - 7.3.2.1 Principle
    - 7.3.2.2 Test machine
      - 7.3.2.2.1 General
      - 7.3.2.2.2 Force correction
    - 7.3.2.3 Test piece
    - 7.3.2.4 Test conditions
      - 7.3.2.4.1 Test temperature
      - 7.3.2.4.2 Conditioning time for test piece
      - 7.3.2.4.3 Compressive force
      - 7.3.2.4.4 Test shear displacement amplitude
      - 7.3.2.4.5 Input wave
      - 7.3.2.4.6 Test vibration velocity
    - 7.3.2.5 Procedure
      - 7.3.2.5.1 Attachment of a test piece
      - 7.3.2.5.2 Loading of test piece
    - 7.3.2.6 Expression of results
    - 7.3.2.7 Test report
  - 7.3.3 Repeated deformation dependence of shear properties
    - 7.3.3.1 Principle
    - 7.3.3.2 Test machine
      - 7.3.3.2.1 General
      - 7.3.3.2.2 Force correction
    - 7.3.3.3 Test piece
    - 7.3.3.4 Test conditions
      - 7.3.3.4.1 Test temperature
      - 7.3.3.4.2 Conditioning time for test piece
      - 7.3.3.4.3 Compressive force
      - 7.3.3.4.4 Test shear displacement amplitude
      - 7.3.3.4.5 Input wave
      - 7.3.3.4.6 Test vibration velocity
    - 7.3.3.5 Procedure
      - 7.3.3.5.1 Attachment of a test piece
      - 7.3.3.5.2 Loading of test piece
    - 7.3.3.6 Expression of results
    - 7.3.3.7 Test report
  - 7.3.4 Temperature dependence of shear properties
    - 7.3.4.1 Principle
    - 7.3.4.2 Test machine
      - 7.3.4.2.1 General
      - 7.3.4.2.2 Force correction

- 7.3.4.3 Test piece
- 7.3.4.4 Test conditions
  - 7.3.4.4.1 Test temperature
  - 7.3.4.4.2 Conditioning time for test piece
  - 7.3.4.4.3 Compressive force
  - 7.3.4.4.4 Test shear displacement amplitude
  - 7.3.4.4.5 Input wave
  - 7.3.4.4.6 Test vibration velocity
- 7.3.4.5 Procedure
  - 7.3.4.5.1 Attachment of a test piece
  - 7.3.4.5.2 Loading of test piece
- 7.3.4.6 Expression of results
- 7.3.4.7 Test report
- 7.3.5 Vertical loading time dependence of shear properties
  - 7.3.5.1 Principle
  - 7.3.5.2 Test machine
    - 7.3.5.2.1 General
    - 7.3.5.2.2 Force correction
  - 7.3.5.3 Test piece
  - 7.3.5.4 Test conditions
    - 7.3.5.4.1 Test temperature
    - 7.3.5.4.2 Conditioning time for test piece
    - 7.3.5.4.3 Compressive force
    - 7.3.5.4.4 Test shear displacement amplitude
    - 7.3.5.4.5 Input wave
    - 7.3.5.4.6 Test vibration velocity
  - 7.3.5.5 Procedure
    - 7.3.5.5.1 Attachment of a test piece
    - 7.3.5.5.2 Loading of test piece
  - 7.3.5.6 Expression of results
  - 7.3.5.7 Test report
- 7.3.6 Dependence of compressive stiffness on compressive stress range
  - 7.3.6.1 Principle
  - 7.3.6.2 Test machine
  - 7.3.6.3 Test piece
  - 7.3.6.4 Test conditions
    - 7.3.6.4.1 Test temperature
    - 7.3.6.4.2 Conditioning time for test piece
    - 7.3.6.4.3 Compressive force
    - 7.3.6.4.4 Input wave
    - 7.3.6.4.5 Test vibration velocity
  - 7.3.6.5 Procedure
    - 7.3.6.5.1 Attachment of a test piece
    - 7.3.6.5.2 Loading of test piece
  - 7.3.6.6 Expression of results
  - 7.3.6.7 Test report
- 7.4 Ultimate shear properties
  - 7.4.1 Principle
  - 7.4.2 Test machine
    - 7.4.2.1 General
      - 7.4.2.1.1 Force correction
  - 7.4.3 Test piece
  - 7.4.4 Test conditions
    - 7.4.4.1 Test temperature
    - 7.4.4.2 Conditioning time for test piece
    - 7.4.4.3 Compressive force
  - 7.4.5 Procedure
    - 7.4.5.1 Attachment of test piece
    - 7.4.5.2 Loading
  - 7.4.6 Expression of results
  - 7.4.7 Test report
- 7.5 Durability testing
  - 7.5.1 Degradation test
    - 7.5.1.1 Principle

- 7.5.1.2 Test machine
- 7.5.1.2.1 Air ageing oven
- 7.5.1.2.2 Compression-shear testing machine
- 7.5.1.3 Test piece
- 7.5.1.4 Test conditions
- 7.5.1.5 Procedure
- 7.5.1.6 Expression of results
- 7.5.1.7 Test report
- 7.5.2 Creep test
- 7.5.2.1 Principle
- 7.5.2.2 Test machine
- 7.5.2.3 Test piece
- 7.5.2.4 Test conditions
- 7.5.2.4.1 Test temperature
- 7.5.2.4.2 Conditioning time for test piece
- 7.5.2.4.3 Compressive force
- 7.5.2.4.4 Total measurement time and measurement intervals
- 7.5.2.5 Procedure
- 7.5.2.5.1 Attachment of test piece and compressive displacement gauges
- 7.5.2.5.2 Loading
- 7.5.2.6 Expression of results
- 7.5.2.7 Test report
- 8 Rubber material tests
- 8.1 Tensile properties tests
- 8.2 Hardness test
- 8.3 Ozone resistance test
- 9 Design rules
- 9.1 General
- 9.2 Elastic sliding bearing
- 9.2.1 Vertical stiffness
- 9.2.2 Horizontal properties
- 9.2.3 Maximum horizontal displacement
- 9.2.4 Maximum compressive load
- 10 Manufacturing tolerances
- 10.1 General
- 10.2 Measuring instruments
- 10.3 Plan dimensions
- 10.3.1 Measurement method
- 10.3.2 Tolerances
- 10.4 Product height
- 10.4.1 Measurement method
- 10.4.2 Tolerances
- 10.5 Flatness
- 10.5.1 Measurement method
- 10.5.1.1 Sliding isolators
- 10.5.1.2 Sliding plate
- 10.5.2 Tolerances
- 10.5.2.1 Sliding isolators
- 10.5.2.2 Sliding plate
- 10.6 Horizontal offset
- 10.7 Plan dimensions of flanges
- 10.8 Flange thickness
- 10.9 Tolerances on positions of flange bolt holes
- 10.10 Dimensions of sliding plate
- 10.11 Thickness of sliding plate
- 11 Marking and labelling
- 11.1 General
- 11.2 Information to be provided
- 11.3 Additional requirements
- 11.4 Marking and labelling examples

12	Test methods
13	Quality assurance

Page count: 43