DIN 7863-1:2022-02 (E)

Elastomer glazing and panel gaskets for windows and claddings - Material requirements - Part 1: Non cellular elastomer glazing and panel gaskets

Contents

Page

Foreword ... 3

1 Scope ... 4

2 Normative references ... 4

3 Terms and definitions ... 5

4 Classification ... 5
4.1 General ... 5
4.2 Temperature classes ... 5
4.3 Hardness classes ... 5

5 Requirements ... 6
5.1 Material requirements ... 6
5.2 Compatibility with adjacent materials ... 10

6 Shape and dimensions of gaskets ... 10

7 Test methods ... 10
7.1 General ... 10
7.2 Hardness ... 10
7.3 Tensile strength and elongation at break ... 10
7.4 Compression set at elevated temperatures ... 10
7.5 Compression set at low temperatures ... 11
7.6 Artificial ageing ... 11
7.6.1 Temperature class –25 °C to +70 °C ... 11
7.6.2 Temperature class –25 °C to +100 °C ... 11
7.6.3 Temperature class –40 °C to +140 °C ... 11
7.7 Change in hardness after cold storage ... 11
7.7.1 Temperature classes –25 °C to +70 °C and –25 °C to +100 °C ... 11
7.7.2 Temperature class –40°C to +140 °C ... 11
7.8 Behaviour after ozone exposure ... 11
7.9 Compatibility with contact media ... 11
7.10 Fire behaviour ... 12

8 Test report ... 12

Tables

Table 1 — Hardness classes ... 5

Table 2 — Material requirements for cladding applications, temperature classes −25 °C to +100 °C and −25 °C to +70 °C ... 7

Table 3 — Material requirements for window applications, temperature classes −25 °C to +100 °C and −25 °C to +70 °C ... 8

Table 4 — Material requirements for window and cladding applications, temperature class −40 °C to +140 °C ... 9