

# ISO 18885-3:2021-11 (E)

## TPMS snap-in valves - Part 3: Performances

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Conditions for testing TPMS snap-in valves .....</b>	<b>2</b>
<b>4.1</b>	<b>General .....</b>	<b>2</b>
<b>4.2</b>	<b>Test fixtures .....</b>	<b>2</b>
<b>4.3</b>	<b>Installation .....</b>	<b>2</b>
<b>4.4</b>	<b>Ageing .....</b>	<b>2</b>
<b>5</b>	<b>Test methods .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Adhesion .....</b>	<b>3</b>
<b>5.2.1</b>	<b>Test method .....</b>	<b>3</b>
<b>5.2.2</b>	<b>Performance .....</b>	<b>3</b>
<b>5.3</b>	<b>Valves core seal .....</b>	<b>3</b>
<b>5.3.1</b>	<b>General .....</b>	<b>3</b>
<b>5.3.2</b>	<b>Room temperature test .....</b>	<b>3</b>
<b>5.3.3</b>	<b>Low temperature test .....</b>	<b>4</b>
<b>5.3.4</b>	<b>High temperature test .....</b>	<b>4</b>
<b>5.4</b>	<b>Valve cap seal (optional, for sealing caps only) .....</b>	<b>4</b>
<b>5.4.1</b>	<b>Test method .....</b>	<b>4</b>
<b>5.4.2</b>	<b>Performance .....</b>	<b>4</b>
<b>5.5</b>	<b>Valve to rim seal .....</b>	<b>5</b>
<b>5.5.1</b>	<b>General .....</b>	<b>5</b>
<b>5.5.2</b>	<b>Low temperature .....</b>	<b>5</b>
<b>5.5.3</b>	<b>High temperature .....</b>	<b>6</b>
<b>5.6</b>	<b>Installation test .....</b>	<b>6</b>
<b>5.6.1</b>	<b>General .....</b>	<b>6</b>
<b>5.6.2</b>	<b>Force to seat .....</b>	<b>6</b>
<b>5.6.3</b>	<b>Force to pull-out only for valve with sensor housing designed to be connected only after valve seating .....</b>	<b>7</b>
<b>5.6.4</b>	<b>Force to pull back (unseating) .....</b>	<b>7</b>
<b>5.7</b>	<b>Burst .....</b>	<b>7</b>
<b>5.7.1</b>	<b>Test method .....</b>	<b>7</b>
<b>5.7.2</b>	<b>Performance .....</b>	<b>7</b>
<b>5.8</b>	<b>Ozone resistance .....</b>	<b>7</b>
<b>5.8.1</b>	<b>Test method .....</b>	<b>7</b>
<b>5.8.2</b>	<b>Performance .....</b>	<b>8</b>
<b>5.9</b>	<b>Flexing resistance .....</b>	<b>8</b>
<b>5.9.1</b>	<b>Test method .....</b>	<b>8</b>
<b>5.9.2</b>	<b>Performance .....</b>	<b>10</b>
<b>5.10</b>	<b>Corrosion test .....</b>	<b>10</b>
<b>5.10.1</b>	<b>Test method .....</b>	<b>10</b>
<b>5.10.2</b>	<b>Performance .....</b>	<b>10</b>
<b>5.11</b>	<b>Valve core torque test .....</b>	<b>11</b>
<b>5.11.1</b>	<b>Test method .....</b>	<b>11</b>
<b>5.11.2</b>	<b>Performance .....</b>	<b>11</b>

<b>5.12</b>	<b>Valve core cycling test .....</b>	<b>11</b>
<b>5.12.1</b>	<b>Test method .....</b>	<b>11</b>
<b>5.12.2</b>	<b>Performance .....</b>	<b>12</b>
<b>5.13</b>	<b>Valve flow rate .....</b>	<b>12</b>
<b>5.13.1</b>	<b>Test method .....</b>	<b>12</b>
<b>5.13.2</b>	<b>Performance .....</b>	<b>12</b>
<b>Bibliography .....</b>		<b>13</b>