

# DIN 7865-2:2022-08 (E)

## Elastomeric-Waterstops for sealing joints in concrete - Part 2: Material specifications and testing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions.....</b>	<b>5</b>
<b>4</b>	<b>Waterstop joints and jointing techniques.....</b>	<b>5</b>
<b>4.1</b>	<b>General .....</b>	<b>5</b>
<b>4.2</b>	<b>Elastomer waterstops with steel strips.....</b>	<b>6</b>
<b>4.3</b>	<b>Elastomer capping joint waterstop .....</b>	<b>6</b>
<b>5</b>	<b>Requirements.....</b>	<b>6</b>
<b>5.1</b>	<b>Properties.....</b>	<b>6</b>
<b>5.2</b>	<b>Rubber-to-metal adhesion .....</b>	<b>7</b>
<b>5.3</b>	<b>Behaviour after conditioning in hot bitumen .....</b>	<b>7</b>
<b>6</b>	<b>Testing .....</b>	<b>7</b>
<b>6.1</b>	<b>Test piece preparation .....</b>	<b>7</b>
<b>6.2</b>	<b>Shore hardness .....</b>	<b>8</b>
<b>6.3</b>	<b>Tensile strength at break and elongation at break.....</b>	<b>8</b>
<b>6.4</b>	<b>Compression set .....</b>	<b>8</b>
<b>6.5</b>	<b>Tear strength.....</b>	<b>8</b>
<b>6.6</b>	<b>Behaviour after heat ageing.....</b>	<b>8</b>
<b>6.7</b>	<b>Change in hardness after cold storage .....</b>	<b>8</b>
<b>6.8</b>	<b>Tension set .....</b>	<b>8</b>
<b>6.9</b>	<b>Rubber-to-metal adhesion .....</b>	<b>8</b>
<b>6.10</b>	<b>Behaviour after conditioning in hot bitumen .....</b>	<b>9</b>
<b>6.11</b>	<b>Behaviour after ozone ageing.....</b>	<b>10</b>
<b>6.12</b>	<b>Bond strength.....</b>	<b>10</b>
<b>7</b>	<b>Marking .....</b>	<b>11</b>

## Figures

Figure 1 — Test piece .....	9
Figure 2 — Test container dimensions .....	10

## Tables

Table 1 — Requirements.....	6
-----------------------------	---