

# ISO 3739-1:2022-10 (E)

## Industrial tyres and rims - Part 1: Pneumatic tyres (metric series) on 5 degrees tapered or flat base rims - Designation, dimensions and marking

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| Foreword .....   |  | iv          |
| <b>1</b>   | <b>Scope .....</b>   | <b>1</b>    |
| <b>2</b>   | <b>Normative references .....</b>                                      | <b>1</b>    |
| <b>3</b>   | <b>Terms and definitions .....</b>                                     | <b>1</b>    |
| <b>4</b>   | <b>Tyre designations .....</b>   | <b>1</b>    |
| <b>4.1</b>   | <b>Dimensional and constructional characteristics .....</b>            | <b>1</b>    |
| <b>4.1.1</b>   | <b>General .....</b>   | <b>1</b>    |
| <b>4.1.2</b>   | <b>Nominal section width .....</b>                                     | <b>2</b>    |
| <b>4.1.3</b>   | <b>Nominal aspect ratio .....</b>                                      | <b>2</b>    |
| <b>4.1.4</b>   | <b>Tyre construction code .....</b>                                    | <b>2</b>    |
| <b>4.1.5</b>   | <b>Nominal rim diameter code .....</b>                                 | <b>2</b>    |
| <b>4.2</b>   | <b>Service description .....</b>                                       | <b>2</b>    |
| <b>4.2.1</b>   | <b>General .....</b>   | <b>2</b>    |
| <b>4.2.2</b>   | <b>Load index .....</b>  | <b>3</b>    |
| <b>4.2.3</b>   | <b>Speed symbol .....</b>  | <b>4</b>    |
| <b>4.3</b>   | <b>Other service characteristics .....</b>                             | <b>5</b>    |
| <b>5</b>   | <b>Marking .....</b>   | <b>5</b>    |
| <b>5.1</b>   | <b>General marking .....</b>   | <b>5</b>    |
| <b>5.2</b>   | <b>Maximum speed marking .....</b>                                     | <b>5</b>    |
| <b>6</b>   | <b>Tyre dimensions .....</b>   | <b>6</b>    |
| <b>6.1</b>   | <b>General .....</b>   | <b>6</b>    |
| <b>6.2</b>   | <b>Calculation of design tyre dimensions .....</b>                     | <b>6</b>    |
| <b>6.2.1</b>   | <b>Nominal aspect ratio, AR .....</b>                                  | <b>6</b>    |
| <b>6.2.2</b>   | <b>Theoretical rim width, Rth .....</b>                                | <b>6</b>    |
| <b>6.2.3</b>   | <b>Design tyre section width, S .....</b>                              | <b>6</b>    |
| <b>6.2.4</b>   | <b>Design tyre section height, H .....</b>                             | <b>6</b>    |
| <b>6.2.5</b>   | <b>Design tyre overall diameter, DO .....</b>                          | <b>6</b>    |
| <b>6.3</b>   | <b>Calculation of maximum overall tyre dimensions in service .....</b> | <b>6</b>    |
| <b>6.3.1</b>   | <b>General .....</b>   | <b>6</b>    |
| <b>6.3.2</b>   | <b>Maximum overall width in service, Wmax .....</b>                    | <b>7</b>    |
| <b>6.3.3</b>   | <b>Maximum overall diameter in service, DO,max .....</b>               | <b>7</b>    |
| <b>7</b>   | <b>Design tyre dimensions .....</b>                                    | <b>7</b>    |
| <b>8</b>   | <b>Tyre size combinations .....</b>                                    | <b>8</b>    |
| <b>9</b>   | <b>Method of measurement of tyre dimensions .....</b>                  | <b>9</b>    |
| <b>Annex A (informative) Tyre size designation .....</b> |  | <b>10</b>   |
| <b>Bibliography .....</b>                                |  | <b>14</b>   |