ISO 3739-1:2022-10 (E)

Industrial tyres and rims - Part 1: Pneumatic tyres (metric series) on 5 degrees tapered or flat base rims - Designation, dimensions and marking

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Tyre designations 1
4.1 Dimensional and constructional characteristics 1
4.1.1 General 1
4.1.2 Nominal section width 2
4.1.3 Nominal aspect ratio 2
4.1.4 Tyre construction code 2
4.1.5 Nominal rim diameter code 2
4.2 Service description 2
4.2.1 General 2
4.2.2 Load index 3
4.2.3 Speed symbol 4
4.3 Other service characteristics 5

5 Marking 5
5.1 General marking 5
5.2 Maximum speed marking 5

6 Tyre dimensions 6
6.1 General 6
6.2 Calculation of design tyre dimensions 6
6.2.1 Nominal aspect ratio, AR 6
6.2.2 Theoretical rim width, Rth 6
6.2.3 Design tyre section width, S 6
6.2.4 Design tyre section height, H 6
6.2.5 Design tyre overall diameter, DO 6
6.3 Calculation of maximum overall tyre dimensions in service 6
6.3.1 General 6
6.3.2 Maximum overall width in service, Wmax 7
6.3.3 Maximum overall diameter in service, DO,max 7

7 Design tyre dimensions 7

8 Tyre size combinations 8

9 Method of measurement of tyre dimensions 9

Annex A (informative) Tyre size designation 10

Bibliography 14