

ISO 583:2023-02 (E)

Conveyor belts with a textile carcass - Total belt thickness and thickness of constitutive elements - Test methods

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Determination of total belt thickness	1
4.1	Apparatus	1
4.2	Test piece	1
4.3	Measurement points	2
4.4	Procedure	3
4.5	Expression of results	3
5	Determination of thickness of covers	3
5.1	General	3
5.2	Method used when covers can be removed completely from carcass	3
5.2.1	Principle	3
5.2.2	Apparatus	3
5.2.3	Test piece	3
5.2.4	Measurement points	3
5.2.5	Procedure	3
5.2.6	Expression of results	4
5.3	Method used when covers cannot be removed completely from carcass	5
5.3.1	Principle	5
5.3.2	Apparatus	5
5.3.3	Test piece	5
5.3.4	Measurement points	5
5.3.5	Procedure	5
5.3.6	Expression of results	6
6	Determination of carcass thickness	6
6.1	Carcass thickness without covers	6
6.2	Carcass thickness with covers	6
6.3	Expression of results	6
7	Determination of thickness of interlayer	7
7.1	General	7
7.2	Method used when elastomeric material in interlayer can be removed completely from adjacent fabric ply	7
7.2.1	Principle	7
7.2.2	Apparatus	7
7.2.3	Test piece	7
7.2.4	Measurement points	7
7.2.5	Procedure	7
7.2.6	Expression of results	7
7.3	Method for use when elastomeric material in interlayer cannot be separated completely from adjacent fabric ply	8
7.3.1	Principle	8
7.3.2	Apparatus	8
7.3.3	Test piece	8
7.3.4	Measurement points	8
7.3.5	Procedure	8
7.3.6	Expression of results	8
8	Test report	8
Bibliography		10