ISO 583:2023-02 (E)

Conveyor belts with a textile carcass - Total belt thickness and thickness of constitutive elements - Test methods

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Determination of total belt thickness 1
4.1 Apparatus 1
4.2 Test piece 1
4.3 Measurement points 2
4.4 Procedure 3
4.5 Expression of results 3

5 Determination of thickness of covers 3
5.1 General 3
5.2 Method used when covers can be removed completely from carcass 3
5.2.1 Principle 3
5.2.2 Apparatus 3
5.2.3 Test piece 3
5.2.4 Measurement points 3
5.2.5 Procedure 3
5.2.6 Expression of results 4
5.3 Method used when covers cannot be removed completely from carcass 5
5.3.1 Principle 5
5.3.2 Apparatus 5
5.3.3 Test piece 5
5.3.4 Measurement points 5
5.3.5 Procedure 5
5.3.6 Expression of results 6

6 Determination of carcass thickness 6
6.1 Carcass thickness without covers 6
6.2 Carcass thickness with covers 6
6.3 Expression of results 6

7 Determination of thickness of interlayer 7
7.1 General 7
7.2 Method used when elastomeric material in interlayer can be removed completely from adjacent fabric ply 7
7.2.1 Principle 7
7.2.2 Apparatus 7
7.2.3 Test piece 7
7.2.4 Measurement points 7
7.2.5 Procedure 7
7.2.6 Expression of results 7
7.3 Method for use when elastomeric material in interlayer cannot be separated completely from adjacent fabric ply 8
7.3.1 Principle 8
7.3.2 Apparatus 8
7.3.3 Test piece 8
7.3.4 Measurement points 8
7.3.5 Procedure 8
7.3.6 Expression of results 8

8 Test report 8

Bibliography 10