

ISO 8066-4:2023-07 (E)

Rubber and plastics hoses and hose assemblies for automotive air conditioning - Specification - Part 4: Low vibration transmission type for Refrigerant 1234yf

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Classification	2
4.1	Construction and material	2
4.2	Pressure class	2
4.3	Moisture-ingression grades	2
5	Dimensions	2
5.1	Hose inside diameters	2
5.2	Hose wall thickness variation	3
6	Testing and performance requirements	3
6.1	Test conditions	3
6.2	Gas leakage	3
6.2.1	Method A for type test and production test	3
6.2.2	Procedure for method A	3
6.2.3	Method B for routine test	3
6.2.4	Procedure for method B	4
6.3	Refrigerant permeation	4
6.3.1	Requirement	4
6.3.2	Procedure	4
6.4	Ageing	4
6.4.1	Requirement	4
6.4.2	Procedure	4
6.5	Low-temperature test	4
6.6	Vacuum resistance	4
6.6.1	General	4
6.6.2	Requirement	4
6.6.3	Procedure	5
6.7	Length change under pressure	5
6.7.1	Requirement	5
6.7.2	Procedure	5
6.8	Minimum bursting pressure	5
6.9	Proof pressure	5
6.10	Extraction by R1234yf	6
6.11	Ozone resistance	6
6.12	Hose cleanliness	6
6.12.1	Requirement	6
6.12.2	Procedure	6
6.13	Impulse test	6
6.13.1	Requirement	6
6.13.2	Procedure	6
6.14	Moisture ingression	7
6.15	Coupling integrity (sealability)	7
6.16	Vibration transmissibility	7

7	Frequency of testing	7
8	Marking	8
9	Test report	8
10	Recommendations for packaging and storage	8
	Annex A (normative) Determination of refrigerant permeation	9
	Annex B (normative) Low-temperature test	12
	Annex C (normative) Determination of amount of matter extracted from hoses by liquid R1234yf	13
	Annex D (normative) Impulse test	14
	Annex E (normative) Moisture ingress test	18
	Annex F (normative) Coupling integrity (sealability)	22
	Annex G (normative) Vibration transmissibility	24
	Annex H (normative) Test frequency	27
	Annex I (informative) Production tests	28
	Bibliography	29