ISO 5775-1:2023-07 (E)

Bicycle tyres and rims - Part 1: Tyre designations and dimensions

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms,definitions,symbolsandabbreviatedterms 1
3.1 Terms and definitions 1
3.2 Symbols and abbreviated terms 2

4 Clincher tyres mounted on straight side or crotchet type rims 2
4.1 Tyre nomenclature 2
4.2 Tyre size designation and marking 3
4.2.1 General 3
4.2.2 Nominal size designation 3
4.2.3 Overall size designation 4
4.2.4 Old size marking 6
4.2.5 Other service characteristics 6
4.2.6 Examples 8
4.3 Tyre dimensions 8
4.3.1 General 8
4.3.2 Design tyre dimensions 8
4.3.3 Tyre measurement method 9
4.3.4 Dimensional specifications 10
4.4 Recommended rim widths in use 11

5 "Beadededge"tyresmountedonhookedbead(HB)rims 12
5.1 General 12
5.2 Tyre designation 12
5.2.1 General 12
5.2.2 Tyre size designation 13
5.2.3 Preferred direction of rotation 13
5.2.4 Example 13
5.3 Tyre dimensions 13
5.3.1 General 13
5.3.2 "Design tyre" dimensions 13
5.3.3 Calculation of maximum tyre dimensions in service 14
5.3.4 Determination of nominal overall diameter code 14
5.3.5 Values 15
5.4 Tyre dimension measurement method 15
5.5 Tyres that can be mounted on both hooked bead (HB) and straight side rims 15
5.5.1 Tyre designation 15
5.5.2 Maximum tyre dimensions in service 15

Annex A (informative) Old size marking 16