ISO 4633:2023-08 (E)

Rubber seals - Joint rings for water supply, drainage and sewerage pipelines - Specification for materials

Contents

Page

Foreword ... iv

1 Scope ... 1

2 Normative references ... 1

3 Terms and definitions ... 2

4 Classification ... 2

5 Requirements ... 2
- 5.1 General ... 2
- 5.2 Effect on water quality ... 2
- 5.3 Microbiological deterioration ... 3
- 5.4 Dimensional tolerances ... 3
- 5.5 Imperfections and defects ... 3
- 5.6 Hardness ... 3
- 5.7 Tensile strength and elongation at break ... 3
- 5.8 Compression set in air ... 3
  - 5.8.1 General ... 3
  - 5.8.2 Compression set at 23 °C and 70 °C ... 4
  - 5.8.3 Low-temperature compression set at –10 °C ... 4
- 5.9 Accelerated ageing in air ... 4
- 5.10 Stress relaxation in compression ... 4
- 5.11 Volume change in water ... 4
- 5.12 Ozone resistance ... 5
- 5.13 Splices of prevulcanized profile ends ... 5
  - 5.13.1 Spliced joints ... 5
  - 5.13.2 Strength of spliced joints ... 5
- 5.14 Summary of physical property requirements ... 5

6 Optional requirements ... 6
- 6.1 Low temperature performance at –25 °C, (type L) ... 6
- 6.2 Volume change in oil, (type O) ... 6
- 6.3 Lifetime estimation, (type LT) ... 6
  - 6.3.1 General ... 6
  - 6.3.2 Method 1 by stress relaxation ... 7
  - 6.3.3 Method 2 by compression set ... 7
- 6.4 Summary of optional property requirements ... 7

7 Test pieces and test temperature ... 8
- 7.1 Preparation of test pieces ... 8
- 7.2 Test temperature ... 8

8 Quality assurance ... 8

9 Storage ... 8

10 Designation ... 8

11 Marking and labelling ... 9

Annex A (normative) **Determination of splice strength** ... 10

Annex B (informative) **Quality assurance** ... 11

Annex C (informative) **Guidance on storage of seals** ... 12

Annex D (informative) **Remarks regarding the lifetime estimation in 6.3** ... 13

Bibliography ... 14