

ISO 24163-2:2024-01 (E)

Clamp-in tyre valves for tyre pressure monitoring systems - Part 2: Test methods and performance

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Test fixture and valve hole dimensions	2
5	Test methods and performance requirements	3
5.1	General	3
5.1.1	Appearance	3
5.1.2	Operating pressure	3
5.1.3	Installation procedure	3
5.1.4	Samples	3
5.2	Leakage test method	3
5.3	Valve core tests	5
5.3.1	Valve core specification for leakage tests	5
5.3.2	Valve core room temperature leakage test	5
5.3.3	Valve core low temperature leakage test	5
5.3.4	Valve core high temperature leakage test	5
5.3.5	Valve core over torque resistance test	6
5.3.6	Valve core endurance test	6
5.3.7	Valve core air flow rate test	7
5.4	Valve cap seal	7
5.4.1	Room temperature test (optional, for sealing caps only)	7
5.5	Valve to rim seal	8
5.5.1	Valve to rim seal leakage test — General	8
5.5.2	Valve to rim seal low temperature leakage test	8
5.5.3	Valve to rim seal high temperature leakage test	8
5.5.4	Valve to rim seal peak temperature leakage test	9
5.6	Valve mechanical resistance	9
5.6.1	Over torque nut test	9
5.6.2	High pressure test	9
5.6.3	Radial force resistance (nose resistance)	9
5.7	Environmental resistance	11
5.7.1	Ozone test	11
5.7.2	Neutral salt spray (NSS) test	12